



Vorto

Vorto IP65 Non Maintained Emergency
Twinspot 500lm 6000K

DESCRIPTION

The Vorto IP65 emergency twin spot with 2 adjustable heads giving a combined 500 lumen output for emergency situations. The Vorto is designed for simple and quick installation with a clip on front cover and the use of push fit terminals perfect for commercial, industrial and warehouse applications.

FEATURES

- Polycarbonate IP65 IK08 construction
- Twin 2.5W LED adjustable and tiltable heads
- Quick fit cover and push fit terminals
- 20mm side entry points
- 3 hour non-maintained manual test function
- LiFePO4 3.2V 5500mAh with 5 year warranty

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.94 kg		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Construction Materials Line 1	Polycarbonate
Dimensions - Height	335 mm	Dimensions - Width	300 mm
Dimensions - Depth	440 mm		

PRODUCT INFORMATION

Wattage Combined	5W	CCT Combined	6000K
Luminaire Lumens Combined	500 lm	lm/W Combined	100 lm/w
Beam Angle	90°	CRI	70
Lumen Maintenance	0.8	IP Rating	IP65
IK Rating	IK08	Emergency Lumen Output	500 lm



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E01VT65EM	Emergency, Non-maintained Emergency, White	5 W	6000 K	500 lm	100 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB32	LiFePO4 3.2V 5500mAh Stick Battery	1 / 10

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	1,073 g
Pallet Layer Qty	42
Pallet Layers	4
Pallet Qty	168
MOM / OPQ	1 / 6