



Skye

Skye Power CCT Switchable IP65 Full Black / Full White / Eyelid Black / Eyelid White Aluminium Bulkhead

DESCRIPTION

The Skye is a durable IP65 aluminium bulkhead. This range is fully adjustable with 3 outputs and 5 colour temperature options. Designed with a polycarbonate diffuser and multiple conduit entries. Available with full and eyelid trims and in a range of variants including emergency, step dim and on/off microwave, to suit a number of applications.

FEATURES

- Power selectable 8W, 14W, 16W
- Colour temperature selectable, 2700K, 3000K, 4000K, 5000K, 6000K
- IP65 and IK10 rating
- Robust Aluminium construction with captive stainless steel screws
- Multiple 20mm conduit entry points with loop in, loop out push fit terminals
- Emergency version: standard or self-test built-in, emergency
- On/off microwave version: on/off function, with adjustable time, lux and detection area
- Step dim version: dip-switch adjustments for daylight

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	2.18 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Die-cast Aluminium base and bezel
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	360 mm
Dimensions - Width	360 mm	Dimensions - Depth	70 mm
IK Rating	IK10	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	8W / 14W / 16W	CCT Combined	2700K / 3000K / 4000K / 5000K / 6000K
Luminaire Lumens Combined	610 - 1200 lm	lm/W Combined	76 - 75 lm/w



Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Displacement Factor	0.9	CCT1/WATT1: Rated Peak Intensity	283 cd
CCT1/WATT2: Rated Peak Intensity	472 cd	CCT1/WATT3: Rated Peak Intensity	535 cd
CCT2/WATT1: Rated Peak Intensity	283 cd	CCT2/WATT2: Rated Peak Intensity	472 cd
CCT2/WATT3: Rated Peak Intensity	535 cd	CCT3/WATT1: Rated Peak Intensity	283 cd
CCT3/WATT2: Rated Peak Intensity	472 cd	CCT3/WATT3: Rated Peak Intensity	535 cd
CCT4/WATT1: Rated Peak Intensity	283 cd	CCT4/WATT2: Rated Peak Intensity	472 cd
CCT4/WATT3: Rated Peak Intensity	535 cd	CCT5/WATT1: Rated Peak Intensity	283 cd
CCT5/WATT2: Rated Peak Intensity	472 cd	CCT4/WATT1: Rated Peak Intensity	535 cd



PACKAGING	
Packaging Type	Brown Box
Individual unit gross weight	2,392 g
Pallet Qty	0
MOM / OPQ	1 / 5

