



## BALTED

PIR Sensor Add-On for BATLED Batten

### DESCRIPTION

PIR Sensor which can be bolted onto the BATLED batten range to enable energy savings when no motion is detected, a simple addition for areas that are not in high use to ensure light is only activated when required

### FEATURES

- Robust Polycarbonate Construction
- Time-On adjustable: 30 secs, 3 mins, 5 mins, 8 mins
- Night & Day or Night Only options selectable
- Detection range 3-6 Metres
- 100° Detection Area

### GENERAL INFORMATION

Colour / Finish	White	Application	Internal
Mounting Type	Surface	Net Weight	0.08 kg

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Operating Temperature (Min)	-20 °C	Operating Temperature (Max)	45 °C
Construction Materials Line 1	Polycarbonate	IP Rating	IP20





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E04BL4AC	4ft	21 W	3000 K	2940 lm	140 lm/W
			4000 K	2940 lm	140 lm/W
			6000 K	2940 lm	140 lm/W
		27 W	3000 K	3780 lm	140 lm/W
			4000 K	3780 lm	140 lm/W
			6000 K	3780 lm	140 lm/W
		32 W	3000 K	4400 lm	0 lm/W
			4000 K	4400 lm	0 lm/W
			6000 K	4400 lm	0 lm/W
		37 W	3000 K	5040 lm	136 lm/W
			4000 K	5040 lm	136 lm/W
			6000 K	5040 lm	136.21621621621622 lm/W
E04BL5AC	5ft	28 W	3000 K	3860 lm	
			4000 K	3860 lm	
			6000 K	3860 lm	
		35 W	3000 K	4860 lm	
			4000 K	4860 lm	
			6000 K	4860 lm	
		43 W	3000 K	5800 lm	0 lm/W
			4000 K	5800 lm	0 lm/W
			6000 K	5800 lm	0 lm/W
		51 W	3000 K	6760 lm	133 lm/W
			4000 K	6760 lm	133 lm/W
			6000 K	6760 lm	132.54901960784315 lm/W
E04BL6AC	6ft	32 W	3000 K	4585 lm	
			4000 K	4585 lm	
			6000 K	4585 lm	
		41 W	3000 K	5800 lm	
			4000 K	5800 lm	
			6000 K	5800 lm	
		50 W	3000 K	6655 lm	0 lm/W
			4000 K	6655 lm	0 lm/W
			6000 K	6655 lm	0 lm/W
		59 W	3000 K	7800 lm	132 lm/W
			4000 K	7800 lm	132 lm/W
			6000 K	7800 lm	132.20338983050848 lm/W

PACKAGING	
Individual unit gross weight	103 g
Pallet Qty	0
MOM / OPQ	1 / 50

