

Verus



Verus 21/27/32/38W Wattage Switchable LED CCT 4ft Linear

DESCRIPTION

The Verus range is available in 4ft, 5ft, 6ft offering both wattage and colour temperature selection. The Verus comes complete with 20mm conduit entry points at both ends and BESA fixing points to the rear. The plug and play emergency and microwave sensor enable further flexibility to suit varying requirements on site.

FEATURES

- High lumen efficiency up to 125lm/W
- Power selectable
- CCT switchable 3000K, 4000K, 6000K
- 20mm conduit entry and BESA fixing points
- Steel housing and opal polycarbonate diffuser
- Plug and play microwave sensor and standard emergency pack available
- Compatible with PANSUSKIT



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	2.04 kg

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polycarbonate	Dimensions - Height	82 mm
Dimensions - Width	199 mm	Dimensions - Depth	1222 mm
IK Rating	IK06	IP Rating	IP20

PRODUCT INFORMATION

Wattage Combined	21W / 27W / 32W / 38W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	2625 - 4750 lm	lm/W Combined	125 - 125 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Emergency Lumen Output	302 lm	Lighting Technology used	LED



Non-Directional or Directional	NDLS	Mains or non-mains	MLS
Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Dimmable	Not Dimmable	Correlated Colour temperature type	STEPS
Displacement Factor	0.9	CCT1/WATT1: Rated Peak Intensity	700 cd
CCT1/WATT2: Rated Peak Intensity	880 cd	CCT1/WATT3: Rated Peak Intensity	1,050 cd
CCT1/WATT4: Rated Peak Intensity	1,220 cd	CCT2/WATT1: Rated Peak Intensity	700 cd
CCT2/WATT2: Rated Peak Intensity	880 cd	CCT2/WATT3: Rated Peak Intensity	1,050 cd
CCT2/WATT4: Rated Peak Intensity	1,250 cd	CCT3/WATT1: Rated Peak Intensity	720 cd
CCT3/WATT2: Rated Peak Intensity	905 cd	CCT3/WATT3: Rated Peak Intensity	1,090 cd
CCT3/WATT4: Rated Peak Intensity	1,280 cd		



IP20



IK06



Colour Temp. Selectable



Power Selectable



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E04VS4AC	4ft	21	3000 K	2625 lm	125 lm/W
			4000 K	2625 lm	125 lm/W
			6000 K	2,625	125 lm/W
		27	3000 K	3375 lm	125 lm/W
			4000 K	3375 lm	125 lm/W
			6000 K	3,375	125 lm/W
		32 W	3000 K	4000 lm	125 lm/W
			4000 K	4000 lm	125 lm/W
			6000 K	4,000	125 lm/W
		38 W	3000 K	4750 lm	125 lm/W
			4000 K	4750 lm	125 lm/W
			6000 K	4750 lm	125 lm/W
E04VS5AC	5ft	32	3000 K	4000 lm	125 lm/W
			4000 K	4000 lm	125 lm/W
			6000 K	4,000	125 lm/W
		41	3000 K	5125 lm	125 lm/W
			4000 K	5125 lm	125 lm/W
			6000 K	5,125	125 lm/W
		50 W	3000 K	6250 lm	125 lm/W
			4000 K	6250 lm	125 lm/W
			6000 K	6,250	125 lm/W
		58 W	3000 K	7250 lm	125 lm/W
			4000 K	7250 lm	125 lm/W
			6000 K	7250 lm	125 lm/W
E04VS6AC	6ft	36	3000 K	4500 lm	125 lm/W
			4000 K	4500 lm	125 lm/W
			6000 K	4,500	125 lm/W
		46	3000 K	5750 lm	125 lm/W
			4000 K	5750 lm	125 lm/W
			6000 K	5,750	125 lm/W
		55 W	3000 K	6875 lm	125 lm/W
			4000 K	6875 lm	125 lm/W
			6000 K	6,875	125 lm/W
		65 W	3000 K	8125 lm	125 lm/W
			4000 K	8125 lm	125 lm/W
			6000 K	8125 lm	125 lm/W



ACCESSORIES

Product Code	Description	MOM / OPQ
E04VSEM	Verus Plug Play 3W Standard Emergency Pack	1 / 40
E04VSMS	Verus Plug Play On / Off Microwave Sensor	1 / 100

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	2,611 g
Pallet Layer Qty	8
Pallet Layers	5



Pallet Qty	40
MOM / OPQ	1 / 4



IP20



IK06



Colour Temp.
Selectable



Power
Selectable

