

## Verus



Verus 32/41/50/58W Wattage Switchable  
LED CCT 5ft Linear

### DESCRIPTION

The Verus range is available in 4ft, 5ft, 6ft offering both wattage and colour temperature selection. The Verus comes complete with 20mm conduit entry points at both ends and BESA fixing points to the rear. The plug and play emergency and microwave sensor enable further flexibility to suit varying requirements on site.

### FEATURES

- High lumen efficiency upto 125lm/W
- Power selectable
- CCT switchable 3000K, 4000K, 6000K
- 20mm conduit entry and Besa fixing points
- Steel housing and opal polycarbonate diffuser
- Plug and play microwave sensor and standard emergency pack available



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	2.53 kg

### TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Steel
Dimensions - Height	82 mm	Dimensions - Width	199 mm
Dimensions - Depth	1522 mm		

### PRODUCT INFORMATION

Wattage Combined	32W / 41W / 50W / 58W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	4000 - 7250 lm	lm/W Combined	125 - 125 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20	IK Rating	IK06



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E04VS4AC	Non-Dimmable, 4ft	21 W	3000 K	2625 lm	125 lm/W
			4000 K	2625 lm	125 lm/W
			6000 K	2625 lm	125 lm/W
		27 W	3000 K	3375 lm	125 lm/W
			4000 K	3375 lm	125 lm/W
			6000 K	3375 lm	125 lm/W
		32 W	3000 K	4000 lm	125 lm/W
			4000 K	4000 lm	125 lm/W
			6000 K	4000 lm	125 lm/W
		38 W	3000 K	4750 lm	125 lm/W
			4000 K	4750 lm	125 lm/W
			6000 K	4750 lm	125 lm/W
E04VS5AC	Non-Dimmable, 5ft	32 W	3000 K	4000 lm	125 lm/W
			4000 K	4000 lm	125 lm/W
			6000 K	4000 lm	125 lm/W
		41 W	3000 K	5125 lm	125 lm/W
			4000 K	5125 lm	125 lm/W
			6000 K	5125 lm	125 lm/W
		50 W	3000 K	6250 lm	125 lm/W
			4000 K	6250 lm	125 lm/W
			6000 K	6250 lm	125 lm/W
		58 W	3000 K	7250 lm	125 lm/W
			4000 K	7250 lm	125 lm/W
			6000 K	7250 lm	125 lm/W
E04VS6AC	Non-Dimmable, 6ft	36 W	3000 K	4500 lm	125 lm/W
			4000 K	4500 lm	125 lm/W
			6000 K	4500 lm	125 lm/W
		46 W	3000 K	5750 lm	125 lm/W
			4000 K	5750 lm	125 lm/W
			6000 K	5750 lm	125 lm/W
		55 W	3000 K	6875 lm	125 lm/W
			4000 K	6875 lm	125 lm/W
			6000 K	6875 lm	125 lm/W
		65 W	3000 K	8125 lm	125 lm/W
			4000 K	8125 lm	125 lm/W
			6000 K	8125 lm	125 lm/W



### ACCESSORIES

Product Code	Description	MOM / OPQ
E04VSEM	Verus Plug Play 3W Standard Emergency Pack	1 / 40
E04VSMS	Verus Plug Play On / Off Microwave Sensor	1 / 100

### PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	3,079 g
Pallet Layer Qty	2
Pallet Layers	5
Pallet Qty	10
MOM / OPQ	1 / 4

