Spec Sheet E04VS6AC

eterna.

5 Year Warranty


IP20


IK06

Colour Temp. Selectable

Power Selectable







Verus

Verus 36/46/55/65W Wattage Switchable LED CCT 6ft Linear

DESCRIPTION

The Verus range is available in 4ft, 5ft, 6ft offering both wattage and colour temperature selection. The Verus comes complete with 20mm conduit entry points at both ends and BESA fixing points to the rear. The plug and play emergency and microwave sensor enable further flexibility to suit varying requirements on site.

FEATURES

- High lumen efficiency upto 125lm/W
- Power selectable
- CCT switchable 3000K, 4000K, 6000K
- 20mm conduit entry and Besa fixing points
- Steel housing and opal polycarbonate diffuser
- Plug and play microwave sensor and standard emergency pack available
- Compatible with PANSUSKIT

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	3.01 kg

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	50,000 h
Number of switching cycles	25,000	**Construction Materials Line 1**	Steel
Construction Materials Line 2	Polycarbonate	**Dimensions - Height**	82 mm
Dimensions - Width	199 mm	**Dimensions - Depth**	1822 mm
IK Rating	IK06	**IP Rating**	IP20

PRODUCT INFORMATION			
Wattage Combined	36W / 46W / 55W / 65W	**CCT Combined**	3000K / 4000K / 6000K
Luminaire Lumens Combined	4500 - 8125 lm	**lm/W Combined**	125 - 125 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Emergency Lumen Output	360 lm	**Lighting Technology used**	LED

CE

UKCA

Member of theLIA

Spec Sheet E04VS6AC

Non-Directional or Directional	NDLS	**Mains or non-mains**	MLS
Connected light source (CLS)	FALSE	**Colour tuneable light source**	FALSE
High Luminance light source	FALSE	**Anti Glare shield**	FALSE
Dimmable	Not Dimmable	**Correlated Colour temperature type**	STEPS
Displacement Factor	0.9	**CCT1/WATT1: Rated Peak Intensity**	1,450 cd
CCT1/WATT2: Rated Peak Intensity	1830 cd	**CCT1/WATT3: Rated Peak Intensity**	2,205 cd
CCT1/WATT4: Rated Peak Intensity	2,570 cd	**CCT2/WATT1: Rated Peak Intensity**	1,475 cd
CCT2/WATT2: Rated Peak Intensity	1,895 cd	**CCT2/WATT3: Rated Peak Intensity**	2,254 cd
CCT2/WATT4: Rated Peak Intensity	2,632 cd	**CCT3/WATT1: Rated Peak Intensity**	1,490 cd
CCT3/WATT2: Rated Peak Intensity	1,900 cd	**CCT3/WATT3: Rated Peak Intensity**	2,260 cd
CCT3/WATT4: Rated Peak Intensity	2,635 cd		

5 Year Warranty

IP20

IK06

Colour Temp. Selectable

Power Selectable

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

eterna.

5 Year Warranty

IP20

IK06

Colour Temp. Selectable

Power Selectable

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
E04VS4AC	4ft	21 W	3000 K	2625 lm	125 lm/W
			4000 K	2625 lm	125 lm/W
			6000 K	2625 lm	125 lm/W
		27 W	3000 K	3375 lm	125 lm/W
			4000 K	3375 lm	125 lm/W
			6000 K	3375 lm	125 lm/W
		32 W	3000 K	4000 lm	125 lm/W
			4000 K	4000 lm	125 lm/W
			6000 K	4000 lm	125 lm/W
		38 W	3000 K	4750 lm	125 lm/W
			4000 K	4750 lm	125 lm/W
			6000 K	4750 lm	125 lm/W
E04VS5AC	5ft	32 W	3000 K	4000 lm	125 lm/W
			4000 K	4000 lm	125 lm/W
			6000 K	4000 lm	125 lm/W
		41 W	3000 K	5125 lm	125 lm/W
			4000 K	5125 lm	125 lm/W
			6000 K	5125 lm	125 lm/W
		50 W	3000 K	6250 lm	125 lm/W
			4000 K	6250 lm	125 lm/W
			6000 K	6250 lm	125 lm/W
		58 W	3000 K	7250 lm	125 lm/W
			4000 K	7250 lm	125 lm/W
			6000 K	7250 lm	125 lm/W
E04VS6AC	6ft	36 W	3000 K	4500 lm	125 lm/W
			4000 K	4500 lm	125 lm/W
			6000 K	4500 lm	125 lm/W
		46 W	3000 K	5750 lm	125 lm/W
			4000 K	5750 lm	125 lm/W
			6000 K	5750 lm	125 lm/W
		55 W	3000 K	6875 lm	125 lm/W
			4000 K	6875 lm	125 lm/W
			6000 K	6875 lm	125 lm/W
		65 W	3000 K	8125 lm	125 lm/W
			4000 K	8125 lm	125 lm/W
			6000 K	8125 lm	125 lm/W

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
E04VSEM	Verus Plug Play 3W Standard Emergency Pack	1 / 40
E04VSMS	Verus Plug Play On / Off Microwave Sensor	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	3,784 g
Pallet Layer Qty	8
Pallet Layers	5

CE

UKCA

Member of theLIA

Pallet Qty	40
MOM / OPQ	1 / 4

5 Year Warranty

IP20

IK06

Colour Temp. Selectable

Power Selectable

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D