



Foris



Foris 28/35/43/50W Wattage Switchable LED CCT Anti-Corrosive 5ft Batten

DESCRIPTION

The Foris anti-corrosive range, available in 4ft, 5ft & 6ft offers both wattage and colour temperature selection enabling 12 combinations into 1 fitting. The Foris comes complete with pre-drilled 20mm conduit entry points (capped), stainless steel retaining clips that require a flat head screw driver to gain access and flexible bracket sliders to suit retrofit positioning. The plug and play emergency and microwave sensor enables further flexibility to suit varying requirements on site.

FEATURES

- High lumen efficiency 150lm/W
- IP65 IK08 rated
- Power selectable
- CCT switchable 3000K, 4000K, 6000K
- 20mm conduit entry at both ends and rear (ends pre drilled and capped)
- Stainless steel clips - flat head screw driver required to gain entry
- Supplied with IP cable grommet, 2 x ceiling brackets
- Plug and play microwave sensor and standard emergency pack available



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Grey
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Net Weight	1.84 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	79 mm	Dimensions - Width	105 mm
Dimensions - Depth	1500 mm		

PRODUCT INFORMATION

Wattage Combined	28W / 35W / 43W / 50W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	4200 - 7500 lm	lm/W Combined	150 - 150 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.7
IP Rating	IP65	IK Rating	IK08



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E05FS4AC	Non-Dimmable, 4ft	17 W	3000 K	2550 lm	150 lm/W
			4000 K	2550 lm	150 lm/W
			6000 K	2550 lm	150 lm/W
		21 W	3000 K	3150 lm	150 lm/W
			4000 K	3150 lm	150 lm/W
			6000 K	3150 lm	150 lm/W
		26 W	3000 K	3900 lm	150 lm/W
			4000 K	3900 lm	150 lm/W
			6000 K	3900 lm	150 lm/W
		30 W	3000 K	4500 lm	150 lm/W
			4000 K	4500 lm	150 lm/W
			6000 K	4500 lm	150 lm/W
E05FS5AC	Non-Dimmable, 5ft	28 W	3000 K	4200 lm	150 lm/W
			4000 K	4200 lm	150 lm/W
			6000 K	4200 lm	150 lm/W
		35 W	3000 K	5250 lm	150 lm/W
			4000 K	5250 lm	150 lm/W
			6000 K	5250 lm	150 lm/W
		43 W	3000 K	6450 lm	150 lm/W
			4000 K	6450 lm	150 lm/W
			6000 K	6450 lm	150 lm/W
		50 W	3000 K	7500 lm	150 lm/W
			4000 K	7500 lm	150 lm/W
			6000 K	7500 lm	150 lm/W
E05FS6AC	Non-Dimmable, 6ft	31 W	3000 K	4650 lm	150 lm/W
			4000 K	4650 lm	150 lm/W
			6000 K	4650 lm	150 lm/W
		40 W	3000 K	6000 lm	150 lm/W
			4000 K	6000 lm	150 lm/W
			6000 K	6000 lm	150 lm/W
		48 W	3000 K	7200 lm	150 lm/W
			4000 K	7200 lm	150 lm/W
			6000 K	7200 lm	150 lm/W
		57 W	3000 K	8550 lm	150 lm/W
			4000 K	8550 lm	150 lm/W
			6000 K	8550 lm	150 lm/W



ACCESSORIES		
Product Code	Description	MOM / OPQ
E04APFSEM	Amplus Foris Plug Play 3W Standard Emergency 1 / 40 Pack	
E04APFSMS	Amplus Foris Plug Play On / Off Microwave Sensor	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	2,056 g
Pallet Layer Qty	4
Pallet Layers	7



Pallet Qty	28
MOM / OPQ	1 / 6



IP65



IK08



Colour Temp.
Selectable



Power
Selectable

