



## Ara


Ara Highbay Microwave Sensor with Corridor Function

### DESCRIPTION

The Ara microwave sensor with corridor function plugs into the centre of the Ara highbay enabling additional energy savings.

### FEATURES

- Zhaga connection plugs into centre of the Ara highbay E07ARA40
- Pre-set program - hold time 1 minute, dims to 10%, 10 minute stand-by period, off (if no further movement detected)
- Suitable for mounting heights upto 15m
- Remote controller E07ARRC to adjust detection range, dim levels, hold times, stand by periods and enabling the daylight sensor
- Conforms to current British and European manufacturing standards, including BS EN 60598



### GENERAL INFORMATION

Colour / Finish	Black	Application	Internal
Product Warranty	5 Years	Net Weight	0.33 kg

### TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Construction Materials Line 1	Polycarbonate
Dimensions - Height	36 mm	Dimensions - Width	50 mm
Dimensions - Depth	50 mm		

### PRODUCT INFORMATION

IP Rating	IP65	IK Rating	IK10
-----------	------	-----------	------





IP65



IK10

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E07ARA40	0-10V Dimmable	90 W	4000 K	16200 lm	180 lm/W
		120 W	4000 K	21600 lm	180 lm/W
		150	4000 K	27000 lm	180 lm/W
E07ARES	Self Test Emergency	5 W	4000 K	515 lm	103 lm/W

## PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	37 g
Pallet Qty	0
MOM / OPQ	1 / 100

