



Atlantic


Atlantic 10W CCT LED IP44 Dual Voltage Shaver Light Chrome

DESCRIPTION

The Atlantic dual voltage shaver light delivers up to 900 lumens and three colour temperature selections. Designed to suit damp locations it comes complete with a self-close cover to the shaver socket and a opal diffuser for even light distribution. The capacitive touch switch removes the need for a pull cord and the 'press to dim' function enables the user to adjust the brightness, a versatile shaver socket to suit single light applications or to compliment existing lighting schemes.

FEATURES

- Dual voltage, switch between 115V - 230V
- IP44 rated, self close socket cover and opal diffuser
- Quick press to adjust CCT 3000K, 4000K, 6500K
- Long press to adjust brightness
- White halo illuminated capacitive switch, halo can be disabled
- Available in gloss white or polished chrome finish
- 5 year warranty



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Polished chrome effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.02 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	ABS
Construction Materials Line 2	Polycarbonate	Dimensions - Height	510 mm
Dimensions - Width	60 mm	Dimensions - Depth	62 mm
IP Rating	IP44		

PRODUCT INFORMATION

Wattage Combined	11W	CCT Combined	3000K / 4000K / 6500K
Luminaire Lumens Combined	900 - 950 lm	lm/W Combined	82 - 86 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Mains Dimmable
Correlated Colour temperature type	STEPS	Chromaticity coordinates x	0.38
Chromaticity coordinates y	0.38	Peak Luminous Intensity (cd)	302 cd
Stroboscopic effect metric (SVM)	0.4	Flicker Metric (pst)	1
R9 colour rendering index	32	Survival factor @6000hrs	0.9
Spectrum report available	Yes	Displacement Factor	0.5
CCT1/WATT1: Rated Peak Intensity	286 cd	CCT2/WATT1: Rated Peak Intensity	286 cd
CCT3/WATT1: Rated Peak Intensity	368 cd		



IP44



Colour Temp. Selectable



PACKAGING

Packaging Type	Brown Box
Individual unit gross weight	360 g
Pallet Qty	0
MOM / OPQ	1 / 20



IP44



Colour Temp.
Selectable

