

Spec Sheet E14AF







110V A-Frame

110V Weatherproof with A-Frame 20W 4000K

IP65

IK08

DESCRIPTION

The 110V anti-corrosive linear batten with A-Frame, comes complete with two integrated 110V sockets, and a 5m cable and plug in socket with cable storage facility.

FEATURES

- High lumen efficiency 120lm/W
- IP65 IK08 rated
- Supplied with 5m cable and pre-wired plug
- Includes 2 x 110V power outlets for connecting more fittings or power tools
- 2 cable tidy hooks on the stand
- Stainless steel clips - flat head screwdriver required to gain entry
- Emergency version available
- 3 year warranty

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Yellow
Application	Internal/External	**Mounting Type**	Surface
Product Warranty	3 years	**Net Weight**	3.26
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	110	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20
Operating Temperature (Max)	45	**Average Rated Life**	50,000
Number of switching cycles	25,000	**Construction Materials Line 1**	ABS
Construction Materials Line 2	Polycarbonate diffuser	**Dimensions - Height**	965
Dimensions - Width	306	**Dimensions - Depth**	650
IK Rating	IK08	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	20W	**CCT Combined**	4000K
Luminaire Lumens Combined	2400 lm	**lm/W Combined**	120 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet E14AF

Lighting Technology used	LED	**Non-Directional or Directional**	NDLS
Mains or non-mains	NMLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	4,000
Chromaticity coordinates x	0.3863	**Chromaticity coordinates y**	0.385
Peak Luminous Intensity (cd)	720 cd	**Stroboscopic effect metric (SVM)**	0.04
Flicker Metric (pst)	0.1	**R9 colour rendering index**	8
Survival factor @6000hrs	0.8	**Spectrum report available**	Yes
Displacement Factor	0.9	**CCT1/WATT1: Rated Peak Intensity**	720

IP65

IK08

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
E14AF	Standard	20 W	4000	2400 lm	120
E14AF1	2 in 1 Switchable Emergency / Self-Test	20 W	4000	2400 lm	120

PACKAGING	
Individual unit gross weight	326
Pallet Qty	0
MOM / OPQ	1 / 1

IP65

IK08

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D