

## 110V 6000K LED Festoon


110V 6000K LED Festoon

### DESCRIPTION

Our connectable festoon kit range includes 12m, 22m and 50m lengths. Each kit includes a male and female connector to daisy chain, and a 1m starter cable, allowing you to link them in any combination up to 200m. This makes on-site extension quick and hassle-free.

### FEATURES

- 12m, 22m and 50m lengths delivering up to 107lm/W
- Polycarbonate site light yellow housing
- 1m starter cable with industrial 3 pin plug
- IP44 IK10
- L70 50,000 hours
- 3 year warranty



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Yellow
Application	Internal/External	Mounting Type	Surface
Product Warranty	3 years	Net Weight	0.38
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	110	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20
Operating Temperature (Max)	45	Average Rated Life	50,000
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	75
Dimensions - Width	75	Dimensions - Depth	63
IK Rating	IK10	IP Rating	IP44

### PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	6000K
Luminaire Lumens Combined	3140 lm	lm/W Combined	105 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lighting Technology used	LED



Non-Directional or Directional	NDLS	Mains or non-mains	MLS
Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Dimmable	Not Dimmable	Correlated Colour temperature type	SINGLE_VALUE
Correlated Colour temperature (K) 1	6,000	Chromaticity coordinates x	0.321
Chromaticity coordinates y	0.34	Peak Luminous Intensity (cd)	117 cd
Stroboscopic effect metric (SVM)	0.04	Flicker Metric (pst)	0.1
R9 colour rendering index	22	Survival factor @6000hrs	0.8
Spectrum report available	Yes	Displacement Factor	0.7
CCT1/WATT1: Rated Peak Intensity	117		



## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E14CF12	12M	30 W	6000	3140 lm	0
E14CF50	50M	100 W	6000	10710 lm	0
E14CF22	22M	50 W	6000	5355 lm	0

## ACCESSORIES

Product Code	Description	MOM / OPQ
E14F2WS	2 Way Festoon Splitter	1 / 0

## PACKAGING

Individual unit gross weight	380
Pallet Qty	0
MOM / OPQ	1 / 4



IP44



IK10

