

Spec Sheet E14CF12

eterna.







110V 6000K LED Festoon

110V 6000K LED Festoon

IP44

IK10

DESCRIPTION

Our connectable festoon kit range includes 12m, 22m and 50m lengths. Each kit includes a male and female connector to daisy chain, and a 1m starter cable, allowing you to link them in any combination up to 200m. This makes on-site extension quick and hassle-free.

FEATURES

- 12m, 22m and 50m lengths delivering up to 107lm/W
- Polycarbonate site light yellow housing
- 1m starter cable with industrial 3 pin plug
- IP44 IK10
- L70 50,000 hours
- 3 year warranty

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Yellow
Application	Internal/External	**Mounting Type**	Surface
Product Warranty	3 years	**Net Weight**	0.38
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	110	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20
Operating Temperature (Max)	45	**Average Rated Life**	50,000
Number of switching cycles	25,000	**Construction Materials Line 1**	Polycarbonate
Construction Materials Line 2	Polycarbonate diffuser	**Dimensions - Height**	75
Dimensions - Width	75	**Dimensions - Depth**	63
IK Rating	IK10	**IP Rating**	IP44

PRODUCT INFORMATION			
Wattage Combined	30W	**CCT Combined**	6000K
Luminaire Lumens Combined	3140 lm	**lm/W Combined**	105 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lighting Technology used**	LED

CE

UK CA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet E14CF12

Non-Directional or Directional	NDLS	**Mains or non-mains**	MLS
Connected light source (CLS)	FALSE	**Colour tuneable light source**	FALSE
High Luminance light source	FALSE	**Anti Glare shield**	FALSE
Dimmable	Not Dimmable	**Correlated Colour temperature type**	SINGLE_VALUE
Correlated Colour temperature (K) 1	6,000	**Chromaticity coordinates x**	0.321
Chromaticity coordinates y	0.34	**Peak Luminous Intensity (cd)**	117 cd
Stroboscopic effect metric (SVM)	0.04	**Flicker Metric (pst)**	0.1
R9 colour rendering index	22	**Survival factor @6000hrs**	0.8
Spectrum report available	Yes	**Displacement Factor**	0.7
CCT1/WATT1: Rated Peak Intensity	117		

IP44

IK10

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
E14CF12	12M	30 W	6000	3140 lm	105
E14CF50	50M	100 W	6000	10710 lm	107
E14CF22	22M	50 W	6000	5355 lm	107

IP44

IK10

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
E14F2WS	2 Way Festoon Splitter	1 / 0

PACKAGING	
Individual unit gross weight	380
Pallet Qty	0
MOM / OPQ	1 / 4