

Spec Sheet E14CF22

eterna.







110V 6000K LED Festoon

110V 6000K LED Festoon

IP44

IK10

DESCRIPTION

Our connectable festoon kit range includes 12m, 22m and 50m lengths. Each kit includes a male and female connector to daisy chain, and a 1m starter cable, allowing you to link them in any combination up to 200m. This makes on-site extension quick and hassle-free.

FEATURES

- 12m, 22m and 50m lengths delivering up to 107lm/W
- Polycarbonate site light yellow housing
- 1m starter cable with industrial 3 pin plug
- IP44 IK10
- L70 50,000 hours
- 3 year warranty

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Yellow
Application	Internal/External	**Mounting Type**	Surface
Product Warranty	3 years	**Net Weight**	0.52
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	110	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20
Operating Temperature (Max)	45	**Average Rated Life**	50,000
Number of switching cycles	25,000	**Construction Materials Line 1**	Polycarbonate
Construction Materials Line 2	Polycarbonate diffuser	**Dimensions - Height**	75
Dimensions - Width	75	**Dimensions - Depth**	63
IK Rating	IK10	**IP Rating**	IP44

PRODUCT INFORMATION			
Wattage Combined	50W	**CCT Combined**	6000K
Luminaire Lumens Combined	5355 lm	**lm/W Combined**	107 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7

CE

UKCA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet E14CF22

Lighting Technology used	LED	**Non-Directional or Directional**	NDLS
Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	6,000
Chromaticity coordinates x	0.321	**Chromaticity coordinates y**	0.34
Peak Luminous Intensity (cd)	117 cd	**Stroboscopic effect metric (SVM)**	0.04
Flicker Metric (pst)	0.1	**R9 colour rendering index**	22
Survival factor @6000hrs	0.8	**Spectrum report available**	Yes
Displacement Factor	0.7	**CCT1/WATT1: Rated Peak Intensity**	117

IP44

IK10

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
E14CF12	12M	30 W	6000	3140 lm	105
E14CF50	50M	100 W	6000	10710 lm	107
E14CF22	22M	50 W	6000	5355 lm	107

IP44

IK10

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
E14F2WS	2 Way Festoon Splitter	1 / 0

PACKAGING	
Packaging Type	Brown Box
Individual unit gross weight	500
Pallet Qty	0
MOM / OPQ	1 / 4