

110V 30W 6000K Globe Light



110V 30W 3050lm 6000K Globe Light

DESCRIPTION

Perfect for construction sites, industrial areas, and outdoor workspaces. Delivering full 360° illumination, this versatile unit can stand freely, mount on a tripod, or hang securely using its integrated hook. An emergency version is also available.

FEATURES

- High lumen efficiency 100lm/W
- IP65 IK10 rated
- Pre-wired with 5m cable with plug
- 1x 110V power outlet for interlinking or power tools
- Built in suspension hook for mounting
- 3 year warranty



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Yellow
Application	Internal/External	Mounting Type	Surface
Product Warranty	3 years	Battery Warranty	3 Years
Net Weight	1.68	Energy Efficiency Class	D

TECHNICAL INFORMATION


Nominal Voltage	110	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20
Operating Temperature (Max)	45	Average Rated Life	50,000
Number of switching cycles	25,000	Construction Materials Line 1	ABS
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	240
Dimensions - Width	190	Dimensions - Depth	190
IK Rating	IK10	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	6000K
Luminaire Lumens Combined	3050 lm	lm/W Combined	102 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Emergency Lumen Output	200	Lighting Technology used	LED
Non-Directional or Directional	NDLS	Mains or non-mains	MLS
Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Dimmable	Not Dimmable	Correlated Colour temperature type	SINGLE_VALUE
Correlated Colour temperature (K) 1	6,000	Chromaticity coordinates x	0.32
Chromaticity coordinates y	0.339	Peak Luminous Intensity (cd)	447 cd
Stroboscopic effect metric (SVM)	0.04	Flicker Metric (pst)	0.1
R9 colour rendering index	7	Survival factor @6000hrs	0.8
Spectrum report available	Yes	Displacement Factor	0.9
CCTI/WATTI: Rated Peak Intensity	447		



PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E14GL	Standard	30 W	6000	3050 lm	102
E14GL1	Emergency	30 W	6000	3050 lm	102

ACCESSORIES

Product Code	Description	MOM / OPQ
E14TRI	Tripod Base for 110V Globe Light	1 / 0

PACKAGING

Packaging Type	Brown Box
Individual unit gross weight	1,480
Pallet Qty	0
MOM / OPQ	1 / 4

