



## 110V 30W 6000K Globe Light



110V 30W 3050lm 6000K Globe Light

### DESCRIPTION

Perfect for construction sites, industrial areas, and outdoor workspaces. Delivering full 360° illumination, this versatile unit can stand freely, mount on a tripod, or hang securely using its integrated hook. An emergency version is also available.

### FEATURES

- High lumen efficiency 100lm/W
- IP65 IK10 rated
- Pre-wired with 5m cable with plug
- 1x 110V power outlet for interlinking or power tools
- Built in suspension hook for mounting
- 3 year warranty



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Yellow
Application	Internal/External	Mounting Type	Surface
Product Warranty	3 years	Net Weight	1.48
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	110	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20
Operating Temperature (Max)	45	Average Rated Life	50,000
Number of switching cycles	25,000	Construction Materials Line 1	ABS
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	240
Dimensions - Width	190	Dimensions - Depth	190
IK Rating	IK10	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	6000K
Luminaire Lumens Combined	3050 lm	lm/W Combined	102 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	6,000
Chromaticity coordinates x	0.32	Chromaticity coordinates y	0.339
Peak Luminous Intensity (cd)	447 cd	Stroboscopic effect metric (SVM)	0.04
Flicker Metric (pst)	0.1	R9 colour rendering index	7
Survival factor @6000hrs	0.8	Spectrum report available	Yes
Displacement Factor	0.9	CCTI/WATT1: Rated Peak Intensity	447



## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E14GL	Standard	30 W	6000	3050 lm	0
E14GL1	Emergency	30 W	6000	3050 lm	0



## ACCESSORIES

Product Code	Description	MOM / OPQ
E14TRI	Tripod Base for I10V Globe Light	1 / 0

## PACKAGING

Individual unit gross weight	1,480
Pallet Qty	0
MOM / OPQ	1 / 4

