


110V CCT IP65 Hoarding Light

110V/240V CCT Switchable IP65 Hoarding Light



DESCRIPTION

The hoarding light offers dual voltage capability operating on both 110V and 240V for maximum flexibility. Choose from opal, prismatic, or red diffuser options. Supplied with a robust mounting bracket meaning the fitting can be installed vertically or horizontally

FEATURES

- Operates in both 110V and 240V
- Robust polycarbonate construction
- Diffuser options opal, prismatic, or red diffusers with a black base
- 7x 20mm cable entries
- Flexible mounting, supplied with a sturdy bracket for vertical or horizontal installation
- 3 year warranty



GENERAL INFORMATION

| | | | |
|-------------------------|-------------------|-----------------|---------|
| Light Source | LED | Colour / Finish | Black |
| Application | Internal/External | Mounting Type | Surface |
| Product Warranty | 3 years | Net Weight | 0.97 |
| Energy Efficiency Class | D | | |

TECHNICAL INFORMATION

| | | | |
|-------------------------------|------------------------|-------------------------------|---------------|
| Nominal Voltage | 110-240 | Frequency | 50Hz |
| Class Protection | 2 | Operating Temperature (Min) | -20 |
| Operating Temperature (Max) | 45 | Average Rated Life | 50,000 |
| Number of switching cycles | 25,000 | Construction Materials Line 1 | Polycarbonate |
| Construction Materials Line 2 | Polycarbonate diffuser | Dimensions - Height | 110 |
| Dimensions - Width | 240 | Dimensions - Depth | 59 |
| IK Rating | IK08 | IP Rating | IP65 |

PRODUCT INFORMATION

| | | | |
|---------------------------|----------------|-------------------|-----------------------|
| Wattage Combined | 10W | CCT Combined | 3000K / 4000K / 6000K |
| Luminaire Lumens Combined | 1350 - 1350 lm | lm/W Combined | 135 - 135 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.7 |



| | | | |
|-------------------------------------|--------|-------------------------------------|--------------|
| Lighting Technology used | LED | Non-Directional or Directional | NDLS |
| Mains or non-mains | MLS | Connected light source (CLS) | FALSE |
| Colour tuneable light source | FALSE | High Luminance light source | FALSE |
| Anti Glare shield | FALSE | Dimmable | Not Dimmable |
| Correlated Colour temperature type | STEPS | Correlated Colour temperature (K) 1 | 3,000 |
| Correlated Colour temperature (K) 2 | 4,000 | Correlated Colour temperature (K) 3 | 6,000 |
| Chromaticity coordinates x | 0.3778 | Chromaticity coordinates y | 0.3725 |
| Peak Luminous Intensity (cd) | 410 cd | Stroboscopic effect metric (SVM) | 0.04 |
| Flicker Metric (pst) | 0.1 | R9 colour rendering index | 18 |
| Survival factor @6000hrs | 0.8 | Spectrum report available | Yes |
| Displacement Factor | 0.9 | CCT1/WATT1: Rated Peak Intensity | 229 |
| CCT2/WATT1: Rated Peak Intensity | 232 | CCT3/WATT1: Rated Peak Intensity | 223 |



PHOTOMETRICS

| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
|--------------|--------------------|-------|------|------------------|------|
| E14HLO | Opal Diffuser | 10 W | 3000 | 1250 lm | 125 |
| | | | 4000 | 1250 lm | 125 |
| | | | 6000 | 1250 lm | 125 |
| E14HLP | Prismatic Diffuser | 10 W | 3000 | 1350 lm | 135 |
| | | | 4000 | 1350 lm | 135 |
| | | | 6000 | 1350 lm | 135 |
| E14HLR | Red Diffuser | 10 W | 3000 | 370 lm | 37 |
| | | | 4000 | 370 lm | 37 |
| | | | 6000 | 370 lm | 37 |

PACKAGING

| | |
|------------------------------|--------|
| Individual unit gross weight | 970 |
| Pallet Qty | 0 |
| MOM / OPQ | 1 / 10 |



IP65



IK08



Colour Temp.
Selectable

