

## 110V CCT IP65 Hoarding Light


110V/240V CCT Switchable IP65 Hoarding Light

### DESCRIPTION

The hoarding light offers dual voltage capability operating on both 110V and 240V for maximum flexibility. Choose from opal, prismatic, or red diffuser options. Supplied with a robust mounting bracket meaning the fitting can be installed vertically or horizontally

### FEATURES

- Operates in both 110V and 240V
- Robust polycarbonate construction
- Diffuser options opal, prismatic, or red diffusers with a black base
- 7x 20mm cable entries
- Flexible mounting, supplied with a sturdy bracket for vertical or horizontal installation
- 3 year warranty



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	Internal/External	Mounting Type	Surface
Product Warranty	3 years	Net Weight	0.97
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	110-240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20
Operating Temperature (Max)	45	Average Rated Life	50,000
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	110
Dimensions - Width	240	Dimensions - Depth	59
IK Rating	IK08	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	10W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	370 - 370 lm	lm/W Combined	37 - 37 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	STEPS	Correlated Colour temperature (K) 1	3,000
Correlated Colour temperature (K) 2	4,000	Correlated Colour temperature (K) 3	6,000
Chromaticity coordinates x	0.3778	Chromaticity coordinates y	0.3725
Peak Luminous Intensity (cd)	410 cd	Stroboscopic effect metric (SVM)	0.04
Flicker Metric (pst)	0.1	R9 colour rendering index	18
Survival factor @6000hrs	0.8	Spectrum report available	Yes
Displacement Factor	0.9	CCT1/WATT1: Rated Peak Intensity	229
CCT2/WATT1: Rated Peak Intensity	232	CCT3/WATT1: Rated Peak Intensity	223



## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E14HLO	Opal Diffuser	10 W	3000	1250 lm	125
			4000	1250 lm	125
			6000	1250 lm	125
E14HLP	Prismatic Diffuser	10 W	3000	1350 lm	135
			4000	1350 lm	135
			6000	1350 lm	135
E14HLR	Red Diffuser	10 W	3000	370 lm	37
			4000	370 lm	37
			6000	370 lm	37



## PACKAGING

Individual unit gross weight	970
Pallet Qty	0
MOM / OPQ	1 / 10

