

110V Uplight


110V 72W 8200lm 6000K Uplight

DESCRIPTION

Ideal for construction sites, industrial areas, and outdoor workspaces, this uplight delivers powerful 360° illumination. It comes pre-wired with a 5m cable with plug, and 110V power outlet for quick setup. Designed with a convenient carry strap, it's the perfect lighting solution for plastering, construction, maintenance, and a wide range of general task applications.

FEATURES

- 360° light distribution
- High lumen efficiency 113lm/W
- IP54 IK10 rated
- Pre-wired with 5m cable with plug
- 1x 110V power outlet for interlinking or power tools
- Convenient carry straps
- 3 year warranty



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Yellow
Application	Internal/External	Mounting Type	Surface
Product Warranty	3 years	Net Weight	3.1
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	110	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20
Operating Temperature (Max)	45	Average Rated Life	50,000
Number of switching cycles	25,000	Construction Materials Line 1	ABS
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	1495
Dimensions - Width	220	Dimensions - Depth	280
IK Rating	IK10	IP Rating	IP54

PRODUCT INFORMATION

Wattage Combined	72W	CCT Combined	4000K
Luminaire Lumens Combined	8200 lm	lm/W Combined	114 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,000
Chromaticity coordinates x	0.383	Chromaticity coordinates y	0.378
Peak Luminous Intensity (cd)	958 cd	Stroboscopic effect metric (SVM)	0.04
Flicker Metric (pst)	0.1	R9 colour rendering index	14
Survival factor @6000hrs	0.8	Spectrum report available	Yes
Displacement Factor	0.9	CCTI/WATT1: Rated Peak Intensity	958



PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E14UP	Standard	72 W	4000	8200 lm	0

PACKAGING

Individual unit gross weight	3,100
Pallet Qty	0
MOM / OPQ	1 / 1



IP54



IK10

