Spec Sheet E14WP4F1MF

eterna.

110V Weatherproof with M/F Connector

110V 20W 4000K LED Anti Corrosive 4FT Emergency Batten with M/F Connector

IP65


IK08

DESCRIPTION

The 110V anti-corrosive linear batten, available in 2ft, 4ft & 5ft comes complete with pre-drilled 20mm conduit entry points (capped), stainless steel retaining clips as standard and flexible bracket sliders to suit retrofit positioning.

FEATURES

- High lumen efficiency 120lm/W
- IP65 IK08 rated
- Pre-wired with 1m cable each side with Male and Female Connector
- Stainless steel clips - flat head screwdriver required to gain entry
- Supplied with 2x ceiling brackets
- 3 year warranty



GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Yellow
Application	Internal/External	**Mounting Type**	Surface, Suspended
Product Warranty	3 years	**Battery Warranty**	3 Years
Net Weight	2.03	**Energy Efficiency Class**	D

TECHNICAL INFORMATION			
Nominal Voltage	110	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20
Operating Temperature (Max)	45	**Average Rated Life**	50,000
Number of switching cycles	25,000	**Construction Materials Line 1**	ABS
Construction Materials Line 2	Polycarbonate diffuser	**Dimensions - Height**	79
Dimensions - Width	85	**Dimensions - Depth**	1200
IK Rating	IK08	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	25W	**CCT Combined**	4000K
Luminaire Lumens Combined	3105 lm	**lm/W Combined**	124 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7

Spec Sheet E14WP4F1MF

Emergency Lumen Output	250	**Lighting Technology used**	LED
Non-Directional or Directional	NDLS	**Mains or non-mains**	MLS
Connected light source (CLS)	FALSE	**Colour tuneable light source**	FALSE
High Luminance light source	FALSE	**Anti Glare shield**	FALSE
Dimmable	Not Dimmable	**Correlated Colour temperature type**	SINGLE_VALUE
Correlated Colour temperature (K) 1	4,000	**Chromaticity coordinates x**	0.3863
Chromaticity coordinates y	0.385	**Peak Luminous Intensity (cd)**	940 cd
Stroboscopic effect metric (SVM)	0.04	**Flicker Metric (pst)**	0.1
R9 colour rendering index	8	**Survival factor @6000hrs**	0.8
Spectrum report available	Yes	**Displacement Factor**	0.9
CCT1/WATT1: Rated Peak Intensity	940		

IP65

IK08

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
E14WP2F1MF	Male/Female Connector	20 W	4000	2400 lm	120
E14WP2FMF	Male/Female Connector	20 W	4000	2400 lm	120
E14WP4F1MF	Male/Female Connector	25 W	4000	3105 lm	124
E14WP4FMF	Male/Female Connector	25 W	4000	3105 lm	124
E14WP5F1MF	Male/Female Connector	35 W	4000	4540 lm	130
E14WP5FMF	Male/Female Connector	35 W	4000	4540 lm	130

PACKAGING	
Packaging Type	Brown Box
Individual unit gross weight	2,030
Pallet Qty	0
MOM / OPQ	1 / 0

IP65

IK08

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D