


110V Weatherproof

110V 35W 4000K LED Anti Corrosive 5FT Batten




DESCRIPTION

The 110V anti-corrosive linear batten, available in 2ft, 4ft & 5ft comes complete with pre-drilled 20mm conduit entry points (capped), stainless steel retaining clips as standard and flexible bracket sliders to suit retrofit positioning.

FEATURES

- High lumen efficiency 120lm/W
- IP65 IK08 rated
- 20mm conduit entry at both ends and rear (ends predrilled and capped)
- Stainless steel clips - flat head screwdriver required to gain entry
- Supplied with IP cable grommet and 2x ceiling brackets
- Emergency version available
- 3 year warranty



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Yellow
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	3 years	Net Weight	1.53
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	110	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20
Operating Temperature (Max)	45	Average Rated Life	50,000
Number of switching cycles	25,000	Construction Materials Line 1	ABS
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	79
Dimensions - Width	85	Dimensions - Depth	1500
IK Rating	IK08	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	35W	CCT Combined	4000K
Luminaire Lumens Combined	4540 lm	lm/W Combined	130 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,000
Chromaticity coordinates x	0.3864	Chromaticity coordinates y	0.335
Peak Luminous Intensity (cd)	1,467 cd	Stroboscopic effect metric (SVM)	0.04
Flicker Metric (pst)	0.1	R9 colour rendering index	8
Survival factor @6000hrs	0.8	Spectrum report available	Yes
Displacement Factor	0.9	CCTI/WATT1: Rated Peak Intensity	1,467



PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E14WP2F	Standard	20 W	4000	2400 lm	120
E14WP2F1	Self Test Emergency, Emergency	20 W	4000	2400 lm	120
E14WP4F	Standard	25 W	4000	3105 lm	124
E14WP4F1	Self Test Emergency, Emergency	25 W	4000	3105 lm	124
E14WP5F	Standard	35 W	4000	4540 lm	130
E14WP5F1	Self Test Emergency, Emergency	35 W	4000	4540 lm	130

PACKAGING

Packaging Type	Brown Box
Individual unit gross weight	1,533
Pallet Qty	0
MOM / OPQ	1 / 6

