



110V Weatherproof with Tripod

110V 20W 4000K LED Anti Corrosive 2FT
Emergency Batten with Tripod





DESCRIPTION

The 110V anti-corrosive linear batten, available in 2ft & 5ft comes complete with pre-wired 5m cable with plug, stainless steel retaining clips as standard and tripod with 2x 110V power outlets

FEATURES

- High lumen efficiency 120lm/w
- IP44 IK08 rated
- Pre-wired with 5m cable with plug
- Stainless steel clips - flat head screwdriver required to gain entry
- Tripod with 2x 110V power outlets
- 3 year warranty



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Yellow
Application	Internal/External	Mounting Type	Surface
Product Warranty	3 years	Battery Warranty	3 Years
Net Weight	4.71	Energy Efficiency Class	D

TECHNICAL INFORMATION

Nominal Voltage	110	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20
Operating Temperature (Max)	45	Average Rated Life	50,000
Number of switching cycles	25,000	Construction Materials Line 1	ABS
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	79
Dimensions - Width	85	Dimensions - Depth	650
IK Rating	IK08	IP Rating	IP44

PRODUCT INFORMATION

Wattage Combined	20W	CCT Combined	4000K
Luminaire Lumens Combined	2400 lm	lm/W Combined	120 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Emergency Lumen Output	250	Lighting Technology used	LED
Non-Directional or Directional	NDLS	Mains or non-mains	MLS
Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Dimmable	Not Dimmable	Correlated Colour temperature type	SINGLE_VALUE
Correlated Colour temperature (K) 1	4,000	Chromaticity coordinates x	0.3863
Chromaticity coordinates y	0.385	Peak Luminous Intensity (cd)	720 cd
Stroboscopic effect metric (SVM)	0.04	Flicker Metric (pst)	0.1
R9 colour rendering index	8	Survival factor @6000hrs	0.8
Spectrum report available	Yes	Displacement Factor	0.9
CCTI/WATTI: Rated Peak Intensity	720		



PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E14WPT2F	Standard	20 W	4000	2400 lm	120
E14WPT2F1	Self Test Emergency, Emergency	20 W	4000	2400 lm	120
E14WPT5F	Standard	35 W	4000	4540 lm	130
E14WPT5F1	Self Test Emergency, Emergency	35 W	4000	4540 lm	130

PACKAGING

Packaging Type	Brown Box
Individual unit gross weight	4,714
Pallet Qty	0
MOM / OPQ	1 / 1



IP44



IK08

