



EBSLIMM

Slim profile maintained/non maintained emergency exit box 5.2W LED 6000K with down, up, left and right signs directive legends

DESCRIPTION

An aesthetically pleasing, low energy, ultra slim alternative to conventional exit boxes. For wall mounting only. 33 metres viewing distance.

FEATURES

- Ultra slim design - excellent solution where a more compact fitting is required
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Facility for remote switching
- Diffuser on base for downward illumination of exit path
- Interchangeable Signs Directive down, left & right arrow exit legends included

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.72 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	26 mm	Dimensions - Width	195 mm
Dimensions - Depth	394 mm	IP Rating	IP20

PRODUCT INFORMATION

Wattage Combined	5.2W	CCT Combined	6000K
Luminaire Lumens Combined	80 lm	lm/W Combined	15 lm/w
Beam Angle	120°	SDCM	<6
Lumen Maintenance	0.8	Emergency Lumen Output	33 lm
Lighting Technology used	LED	Non-Directional or Directional	NDLS





IP20

Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	6,500
Chromaticity coordinates x	0.3064	Chromaticity coordinates y	0.3831
R9 colour rendering index	0	Networked Standby Power	0
Displacement Factor	0.33		





IP20

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
EBLSLIMM	Emergency	5.2 W	6000 K	80 lm	15 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
EB7	Ni-Mh 3.6V 2000mAh Side-by-side Battery	1 / 1

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	875 g
Pallet Layer Qty	60
Pallet Layers	5
Pallet Qty	300
MOM / OPQ	1 / 10

