



## EBSLIMM

Slim profile maintained/non maintained emergency exit box 5.2W LED 6000K with down, up, left and right signs directive legends

### DESCRIPTION

An aesthetically pleasing, low energy, ultra slim alternative to conventional exit boxes. For wall mounting only. 33 metres viewing distance.

### FEATURES

- Ultra slim design - excellent solution where a more compact fitting is required
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Facility for remote switching
- Diffuser on base for downward illumination of exit path
- Interchangeable Signs Directive down, left & right arrow exit legends included

### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.72 kg		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	26 mm	Dimensions - Width	195 mm
Dimensions - Depth	394 mm	IP Rating	IP20

### PRODUCT INFORMATION

Wattage Combined	5.2W	CCT Combined	6000K
Luminaire Lumens Combined	80 lm	lm/W Combined	15 lm/w
Beam Angle	120°	SDCM	<6
Lumen Maintenance	0.8	Emergency Lumen Output	33 lm
Lighting Technology used	LED	Non-Directional or Directional	NDLS





IP20

Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	6,500
Chromaticity coordinates x	0.3064	Chromaticity coordinates y	0.3831
R9 colour rendering index	0	Networked Standby Power	0
Displacement Factor	0.33		





IP20

### PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
EBLSLIMM	Emergency	5.2	6000 K	80 lm	15 lm/W

### ACCESSORIES

Product Code	Description	MOM / OPQ
EB7	Ni-Mh 3.6V 2000mAh Side-by-side Battery	1 / 1

### PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	875 g
Pallet Layer Qty	60
Pallet Layers	5
Pallet Qty	300
MOM / OPQ	1 / 10

