Spec Sheet EBLSLIMM

5 Year Warranty

IP20



EBLSLIMM

Slim profile maintained/non maintained emergency exit box 5.2W LED 6000K with down, up, left and right signs directive legends

DESCRIPTION

An aesthetically pleasing, low energy, ultra slim alternative to conventional exit boxes. For wall mounting only. 33 metres viewing distance.

FEATURES

- Ultra slim design - excellent solution where a more compact fitting is required
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Facility for remote switching
- Diffuser on base for downward illumination of exit path
- Interchangeable Signs Directive down, left & right arrow exit legends included



GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal	**Mounting Type**	Surface
Product Warranty	5 Years	**Battery Warranty**	1 Year
Net Weight	0.72 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50-60Hz
Class Protection	1	**Operating Temperature (Min)**	0 °C
Operating Temperature (Max)	40 °C	**Average Rated Life**	30,000 h
Number of switching cycles	15,000	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	26 mm	**Dimensions - Width**	195 mm
Dimensions - Depth	394 mm	**IP Rating**	IP20

PRODUCT INFORMATION			
Wattage Combined	5.2W	**CCT Combined**	6000K
Luminaire Lumens Combined	80 lm	**lm/W Combined**	15 lm/w
Beam Angle	120°	**SDCM**	<6
Lumen Maintenance	0.8	**Emergency Lumen Output**	33 lm
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet EBLSLIMM

5 Year Warranty

IP20

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	6,500
Chromaticity coordinates x	0.3064	**Chromaticity coordinates y**	0.3831
R9 colour rendering index	0	**Networked Standby Power**	0
Displacement Factor	0.33		

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
EBLSLIMM	Emergency	5.2 W	6000 K	80 lm	15 lm/W

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
EB7	Ni-Mh 3.6V 2000mAh Side-by-side Battery	1 / 1

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	875 g
Pallet Layer Qty	60
Pallet Layers	5
Pallet Qty	300
MOM / OPQ	1 / 10