Spec Sheet EBLSLIMM











393mm

EBLSLIMM

Slim profile maintained/non maintained emergency exit box 5.2W LED 6000K with down, up, left and right signs directive legends

DESCRIPTION

An aesthetically pleasing, low energy, ultra slim alternative to conventional exit boxes. For wall mounting only. 33 metres viewing distance.

FEATURES

- Ultra slim design excellent solution where a more compact fitting is required
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- · Facility for remote switching
- Diffuser on base for downward illumination of exit path
- Interchangeable Signs Directive down, left & right arrow exit legends included

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.72 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 ℃
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	26 mm	Dimensions - Width	195 mm
Dimensions - Depth	394 mm		

PRODUCT INFORMATION			
Wattage Combined	5.2W	CCT Combined	6000K
Luminaire Lumens Combined	80 lm	lm/W Combined	15 lm/w
Beam Angle	120°	SDCM	<6
Lumen Maintenance	0.8	IP Rating	IP20
Emergency Lumen Output	33 lm		
















IP20	

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB7	Ni-Mh 3.6V 2000mAh Side-by-side Battery	1/1

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	875 g
Pallet Layer Qty	60
Pallet Layers	5
Pallet Qty	300
MOM / OPQ	1 / 10







