



30W LED Floodlight


30W 2100lm LED Floodlight

DESCRIPTION

30W LED slimline floodlight achieving 2100lm at 4000K, wall bracket provided for quick installation

FEATURES

- Pre-wired with 80cm cable
- Attractive slimline design
- 4000K colour temperature



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Net Weight	0.88 kg	Energy Efficiency Class	F

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Construction Materials Line 1	Aluminium	Construction Materials Line 2	Glass
Dimensions - Height	155 mm	Dimensions - Width	187 mm
Dimensions - Depth	50 mm	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	4000K
Luminaire Lumens Combined	2200 lm	lm/W Combined	73 lm/w
Beam Angle	100°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Dimmable	Not Dimmable	CCT1/WATT1: Rated Peak Intensity	965 cd





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
ELEDFLD10	Standard	10 W	4000 K	1000 lm	100 lm/W
ELEDFLD30	Standard	30 W	4000 K	2200 lm	73 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	952 g
Pallet Layer Qty	105
Pallet Layers	4
Pallet Qty	420
MOM / OPQ	1 / 15

