




5FT LED Twin Ceiling Fitting
5FT LED Twin Slimline Ceiling Fitting

DESCRIPTION

A slim, modern design LED ceiling fitting which offers a more stylish alternative to traditional battens. Where a more aesthetically pleasing fixture is desirable this versatile and elegant light source is suitable for commercial, retail and domestic applications.

FEATURES

- 100 lm/W
- Push terminal connections
- Emergency version utilises the LDLEM3



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	2.1 kg

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	20,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	Polycarbonate	Dimensions - Height	43 mm
Dimensions - Width	127 mm	Dimensions - Depth	1503 mm

PRODUCT INFORMATION

Wattage Combined	50W	CCT Combined	4000K
Luminaire Lumens Combined	5000 lm	lm/W Combined	100 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.9
IP Rating	IP20		



PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
ELEGAN5EM3	Standard	50 W	4000 K	5000 lm	100 lm/W
ELEGANCE5	Standard	50 W	4000 K	5000 lm	100 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
ELESUSPACK	ELEGANCE5 Suspension Kit	1 / 100

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	2,467 g
Pallet Layer Qty	18
Pallet Layers	7
Pallet Qty	126
MOM / OPQ	1 / 6

