Spec Sheet ELEGANCE5

5 Year Warranty

IP20



5FT LED Twin Ceiling Fitting

5FT LED Twin Slimline Ceiling Fitting


DESCRIPTION

A slim, modern design LED ceiling fitting which offers a more stylish alternative to traditional battens. Where a more aesthetically pleasing fixture is desirable this versatile and elegant light source is suitable for commercial, retail and domestic applications.

FEATURES

- 100 lm/W
- Push terminal connections
- Emergency version utilises the LDLEM3





GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	2.1 kg

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	0 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	40,000 h
Number of switching cycles	20,000	**Construction Materials Line 1**	Aluminium
Construction Materials Line 2	Polycarbonate	**Dimensions - Height**	43 mm
Dimensions - Width	127 mm	**Dimensions - Depth**	1503 mm
IP Rating	IP20		

PRODUCT INFORMATION			
Wattage Combined	50W	**CCT Combined**	4000K
Luminaire Lumens Combined	5000 lm	**lm/W Combined**	100 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.9
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

CE

UKCA

Member of theLIA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet ELEGANCE5

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	4,000
Chromaticity coordinates x	0.379	**Chromaticity coordinates y**	0.378
Stroboscopic effect metric (SVM)	0.1	**Flicker Metric (pst)**	1.0
R9 colour rendering index	15.0	**Survival factor @6000hrs**	0.9
Claim LED Replace Fluorescent	FALSE	**Spectrum report available**	Yes
Displacement Factor	0.94	**CCT1/WATT1: Rated Peak Intensity**	1,353 cd

5 Year Warranty

IP20

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

eterna.

5 Year Warranty

IP20

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
ELEGAN5EM3	Standard	50 W	4000 K	5000 lm	100 lm/W
ELEGANCE5	Standard	50 W	4000 K	5000 lm	100 lm/W

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
ELESUSPACK	ELEGANCE5 Suspension Kit	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	2,467 g
Pallet Layer Qty	18
Pallet Layers	7
Pallet Qty	126
MOM / OPQ	1 / 6

CE

UK CA