
Spec Sheet EML3NMISO

5 Year Warranty

IP65





EML3NMISO

Non-maintained IP65 Emergency bulkhead 7W LED 6000K with ISO 7010 legend set

DESCRIPTION

High power non maintained emergency bulkhead incorporating 3 rows of LEDs for higher output and a more even distribution across the fixture. Supplied as standard with ISO7010 legends set.

FEATURES

- Hinged gear tray & push fit terminal block - allows for quicker and easier installation and maintenance
- 20mm gland entries as standard
- Internal or external use
- Viewing distance 20m
- High output LEDs with bright white light
- 3 hour duration in emergency mode
- Dedicated self adhesive ISO 7010 legend pack included with a combination of symbols. Allows multiple exit path designation options
- Ni-Cd 3.6V 1500mAh battery 1 year warranty - Replacement battery code: EB1

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal/External	**Mounting Type**	Surface, Recessed
Product Warranty	5 Years	**Battery Warranty**	1 Year
Net Weight	0.83 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50-60Hz
Operating Temperature (Min)	25 °C	**Operating Temperature (Max)**	40 °C
Average Rated Life	30,000 h	**Number of switching cycles**	15,000
Construction Materials Line 1	Polycarbonate	**Dimensions - Height**	110 mm
Dimensions - Width	355 mm	**Dimensions - Depth**	70 mm
IP Rating	IP65		

PRODUCT INFORMATION			
Wattage Combined	2W	**CCT Combined**	6000K
Luminaire Lumens Combined	150 lm	**lm/W Combined**	75 lm/w
Beam Angle	120°	**CRI**	75
SDCM	<6	**Lumen Maintenance**	0.8
Emergency Lumen Output	170 lm	**Dimmable**	Not Dimmable

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

CCT1/WATT1: Rated Peak Intensity	39 cd		

5 Year Warranty

IP65

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
EML3MISO	Maintained Emergency, ISO Legends Set	7 W	6000 K	320 lm	46 lm/W
EML3NMISO	Non-maintained Emergency, ISO Legends Set	2 W	6000 K	150 lm	75 lm/W
EMLED3M	Maintained Emergency, Signs Directive Set	4 W	6000 K	350 lm	88 lm/W
EMLED3NM	Non-maintained Emergency, Signs Directive Set	2 W	6000 K	150 lm	75 lm/W

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
EB1	Ni-Cd 3.6V 1500mAh Stick Battery	1 / 1
BULKFRAME	Semi-Recessed Emergency Bulkhead White Frame	1 / 12
ISOLGDSET	ISO Legend Set for Emergency Bulkheads	1 / 12
LGDSET	Legend Set For EM Bulkhead	1 / 12

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	778 g
Pallet Layer Qty	72
Pallet Layers	5
Pallet Qty	360
MOM / OPQ	1 / 12