







Maintained IP65 Emergency bulkhead 4W LED 6000K with signs directive legend set

## DESCRIPTION

High power maintained emergency bulkhead incorporating 3 rows of LEDs for higher output and a more even distribution across the fixture. Supplied as standard with Signs Directive legends set.

## **FEATURES**

- Hinged gear tray & push fit terminal block allows for quicker and easier installation and maintenance
- 20mm gland entries as standard
- · Internal or external use
- · Viewing distance 20m
- High output LEDs 350 lumens in mains mode and 200 lumens in emergency mode
- 3 hour duration in emergency mode
- Dedicated self adhesive Signs Directive legend pack included with a combination of symbols. Allows multiple exit path designation options
- LiFePO4 1500mAh 5 year warranty





GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface, Recessed
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.83 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	110 mm	Dimensions - Width	355 mm
Dimensions - Depth	70 mm		

PRODUCT INFORMATION			
Wattage Combined	4W	CCT Combined	6000K
Luminaire Lumens Combined	350 lm	lm/W Combined	88 lm/w
Beam Angle	120°	CRI	70
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP65	Emergency Lumen Output	172 lm
















ACCESSORIES		
Product Code	Description	MOM / OPQ
EB1	Ni-Cd 3.6V 1500mAh Stick Battery	1/1
BULKFRAME	Semi-Recessed Emergency Bulkhead White	1 / 12
	Frame	
ISOLGDSET	ISO Legend Set for Emergency Bulkheads	1 / 12
LGDSET	Legend Set For EM Bulkhead	12 / 12
	<u> </u>	

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	931 g	
Pallet Layer Qty	72	
Pallet Layers	5	
Pallet Qty	360	
MOM / OPQ	1 / 12	







