



## EMLED3NM



Non-maintained IP65 Emergency bulkhead  
2W LED 6000K with signs directive legend set

### DESCRIPTION

High power non maintained emergency bulkhead incorporating 3 rows of LEDs for higher output and a more even distribution across the fixture. Supplied as standard with Signs Directive legends set.

### FEATURES

- Hinged gear tray & push fit terminal block - allows for quicker and easier installation and maintenance
- 20mm gland entries as standard
- Internal or external use
- Viewing distance 20m
- High output LEDs with bright white light
- 3 hour duration in emergency mode
- Dedicated self adhesive Signs Directive legend pack included with a combination of symbols. Allows multiple exit path designation options
- LiFePO4 3.2V 1500mAh battery 5 year warranty



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface, Recessed
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.83 kg		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	110 mm	Dimensions - Width	355 mm
Dimensions - Depth	70 mm	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	2W	CCT Combined	6000K
Luminaire Lumens Combined	150 lm	lm/W Combined	75 lm/w
Beam Angle	120°	CRI	75
SDCM	<6	Lumen Maintenance	0.8
Emergency Lumen Output	170 lm	Lighting Technology used	LED





**IP65**

<b>Non-Directional or Directional</b>	NDLS	<b>Mains or non-mains</b>	MLS
<b>Connected light source (CLS)</b>	FALSE	<b>Colour tuneable light source</b>	FALSE
<b>High Luminance light source</b>	FALSE	<b>Anti Glare shield</b>	FALSE
<b>Dimmable</b>	Not Dimmable	<b>Correlated Colour temperature type</b>	SINGLE_VALUE
<b>Correlated Colour temperature (K) 1</b>	6,000	<b>Displacement Factor</b>	0
<b>CCTI/WATTI: Rated Peak Intensity</b>	39 cd		





IP65

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
EML3MISO	Maintained Emergency, ISO Legends Set	7 W	6000 K	320 lm	46 lm/W
EML3NMISO	Non-maintained Emergency, ISO Legends Set	2 W	6000 K	150 lm	75 lm/W
EMLED3M	Maintained Emergency, Signs Directive Set	4 W	6000 K	350 lm	88 lm/W
EMLED3NM	Non-maintained Emergency, Signs Directive Set	2 W	6000 K	150 lm	75 lm/W

## ACCESSORIES

Product Code	Description	MOM / OPQ
EBI	Ni-Cd 3.6V 1500mAh Stick Battery	1 / 1
BULKFRAME	Semi-Recessed Emergency Bulkhead White Frame	1 / 12
ISOLGDSET	ISO Legend Set for Emergency Bulkheads	1 / 12
LGDSET	Legend Set For EM Bulkhead	1 / 12

## PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	766 g
Pallet Layer Qty	72
Pallet Layers	5
Pallet Qty	360
MOM / OPQ	1 / 12

