

## EXIT3MLED


Maintained 4W white emergency exit box with signs directive down arrow legend

### DESCRIPTION

Low energy alternative to standard emergency exit signs, robust steel construction with traditional battery test button for easy access, suitable to be adjusted for non-maintained operation to suit a number of commercial and industrial applications

### FEATURES

- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Facility for remote switching
- Viewing distance: 32m
- LED charge light & battery test button
- Diffuser on base for downward illumination of exit path
- 55 lumens in mains mode
- Interchangeable polycarbonate Down arrow exit legend included. Full range of alternative legend directional panels available
- LiFePO4 1500mAh - 5 year warranty



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	1.47 kg		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polycarbonate down arrow legend	Dimensions - Height	192 mm
Dimensions - Width	390 mm	Dimensions - Depth	60 mm
IP Rating	IP20		

### PRODUCT INFORMATION

Wattage Combined	4W	CCT Combined	6500K
Luminaire Lumens Combined	55 lm	lm/W Combined	14 lm/w
Beam Angle	110°	CRI	79



SDCM	<6	Lumen Maintenance	0.8
Emergency Lumen Output	17 lm	Dimmable	Not Dimmable



IP20





IP20

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
EXIT3MLED	Emergency	4 W	6500 K	55 lm	14 lm/W
SEEXIT3ML	Emergency	4 W	6500 K	55 lm	14 lm/W

## ACCESSORIES

Product Code	Description	MOM / OPQ
EB4	Ni-Cd 3.6V 1500mAh Side-by-side Battery	1 / 1
EBLGDL	Left Arrow Legend for Exitboxes	1 / 100
EBLGDR	Right Arrow Legend for Exitboxes	1 / 100
EBLGDU	Up Arrow Legend for Exitboxes	1 / 100
ISOEBLGDD	ISO Down Arrow Legend for Emergency Exitboxes	1 / 1
ISOEBLGDL	ISO Left Arrow Legend for Emergency Exitboxes	1 / 1
ISOEBLGDR	ISO Right Arrow Legend for Emergency Exitboxes	1 / 1
ISOEBLGDU	ISO Up Arrow Legend for Emergency Exitboxes	1 / 1

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,500 g
Pallet Layer Qty	60
Pallet Layers	3
Pallet Qty	180
MOM / OPQ	1 / 6

