



EXIT3MLED

Maintained 4W white emergency exit box with signs directive down arrow legend

DESCRIPTION

Low energy alternative to standard emergency exit signs, robust steel construction with traditional battery test button for easy access, suitable to be adjusted for non-maintained operation to suit a number of commercial and industrial applications

FEATURES

- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Facility for remote switching
- Viewing distance: 32m
- LED charge light & battery test button
- Diffuser on base for downward illumination of exit path
- 55 lumens in mains mode
- Interchangeable polycarbonate Down arrow exit legend included. Full range of alternative legend directional panels available
- Ni-Cd 3.6V 1500Ah battery 1 year warranty - Replacement battery code: EB4

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	1.47 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polycarbonate down arrow legend	Dimensions - Height	192 mm
Dimensions - Width	390 mm	Dimensions - Depth	60 mm

PRODUCT INFORMATION			
Wattage Combined	4W	CCT Combined	6500K
Luminaire Lumens Combined	55 lm	lm/W Combined	14 lm/w
Beam Angle	110°	CRI	79
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP20		





PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
EXIT3MLED	Emergency	4 W	6500 K	55 lm	14 lm/W
SEEXIT3ML	Emergency	4 W	6500 K	55 lm	14 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
EB4	Ni-Cd 3.6V 1500mAh Side-by-side Battery	1 / 1
EBLGDL	Left Arrow Legend for Exitboxes	1 / 100
EBLGDR	Right Arrow Legend for Exitboxes	1 / 100
EBLGDU	Up Arrow Legend for Exitboxes	1 / 100
ISOEBLGDD	ISO Down Arrow Legend for Emergency Exitboxes	1 / 1
ISOEBLGDL	ISO Left Arrow Legend for Emergency Exitboxes	1 / 1
ISOEBLGDR	ISO Right Arrow Legend for Emergency Exitboxes	1 / 1
ISOEBLGDU	ISO Up Arrow Legend for Emergency Exitboxes	1 / 1

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,500 g
Pallet Layer Qty	60
Pallet Layers	3
Pallet Qty	180
MOM / OPQ	1 / 6

