




23W Low Energy Floodlight  
23W Max Low Energy Polycarbonate Floodlight

DESCRIPTION

Energy efficient alternative to traditional halogen floodlights, with corrosion resistant polycarbonate housing. The use of E27 CFLi as the light source allows easy, economic lamp replacement by the end user. Available with or without PIR switching.

FEATURES

- Uses self ballasted low energy lamp
- Lamp replacements can be easily sourced by the end user
- Adjustable mounting bracket
- Low energy consumption
- Practical, modern alternative to halogen floodlights



GENERAL INFORMATION

Light Source	Non Integral	Colour / Finish	Black
Application	External	Mounting Type	Surface
Net Weight	0.99 kg	Energy Efficiency Class	G

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	1	Average Rated Life	10,000 h
Construction Materials Line 1	Polycarbonate	Dimensions - Height	136 mm
Dimensions - Width	215 mm	Dimensions - Depth	100 mm

PRODUCT INFORMATION

Wattage Combined	23W	CCT Combined	6400K
Luminaire Lumens Combined	1370 lm	lm/W Combined	60 lm/w
CRI	80	Lumen Maintenance	0.7
IP Rating	IP44		



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
FL124B	Standard	23 W	6400 K	1370 lm	60 lm/W
FL157B	Standard	57 W	6400 K	4275 lm	75 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	1,166 g
Pallet Qty	0
MOM / OPQ	1 / 0

