



30W LED Floodlight


30W White LED Floodlight 2400lm 4000K

DESCRIPTION

30W LED Floodlight

FEATURES

- Aluminium & polycarbonate construction
- Horizontally and vertically adjustable bracket
- Detachable bracket allowing easy installation
- Fixed IP rated connector for wiring direct to the floodlight
- Terminal Connector can be removed for ease of wiring



GENERAL INFORMATION

| | | | |
|-------------------------|----------|-----------------|---------|
| Light Source | LED | Colour / Finish | White |
| Application | External | Mounting Type | Surface |
| Product Warranty | 5 Years | Net Weight | 0.60 kg |
| Energy Efficiency Class | F | | |

TECHNICAL INFORMATION

| | | | |
|-------------------------------|-----------|-------------------------------|--------|
| Nominal Voltage | 240 | Frequency | 50Hz |
| Class Protection | 1 | Operating Temperature (Max) | 0 °C |
| Average Rated Life | 25,000 h | Number of switching cycles | 12,500 |
| Construction Materials Line 1 | Aluminium | Construction Materials Line 2 | ABS |
| Dimensions - Height | 128 mm | Dimensions - Width | 179 mm |
| Dimensions - Depth | 119 mm | IP Rating | IP65 |

PRODUCT INFORMATION

| | | | |
|---------------------------|---------|--------------------------------|---------|
| Wattage Combined | 30W | CCT Combined | 4000K |
| Luminaire Lumens Combined | 2400 lm | lm/W Combined | 80 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.7 |
| Lighting Technology used | LED | Non-Directional or Directional | NDLS |



| | | | |
|----------------------------------|--------|------------------------------|--------------|
| Mains or non-mains | MLS | Connected light source (CLS) | FALSE |
| Colour tuneable light source | FALSE | High Luminance light source | FALSE |
| Anti Glare shield | FALSE | Dimmable | Not Dimmable |
| CCT1/WATT1: Rated Peak Intensity | 764 cd | | |



IP65





| PHOTOMETRICS | | | | | |
|--------------|--------------|-------|--------|------------------|---------|
| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
| FLD10BK | Standard | 10 W | 4000 K | 800 lm | 80 lm/W |
| FLD10PIRBK | PIR | 10 W | 4000 K | 800 lm | 80 lm/W |
| FLD10PIRWH | PIR | 10 W | 4000 K | 800 lm | 80 lm/W |
| FLD10WH | Standard | 10 W | 4000 K | 800 lm | 80 lm/W |
| FLD20BK | Standard | 20 W | 4000 K | 1600 lm | 80 lm/W |
| FLD20PIRWH | PIR | 20 W | 4000 K | 1600 lm | 80 lm/W |
| FLD20WH | Standard | 20 W | 4000 K | 1600 lm | 80 lm/W |
| FLD30BK | Standard | 30 W | 4000 K | 2400 lm | 80 lm/W |
| FLD30PIRBK | PIR | 30 W | 4000 K | 2400 lm | 80 lm/W |
| FLD30PIRWH | PIR | 30 W | 4000 K | 2400 lm | 80 lm/W |
| FLD30WH | Standard | 30 W | 4000 K | 2400 lm | 80 lm/W |
| FLD50BK | Standard | 50 W | 4000 K | 4000 lm | 80 lm/W |
| FLD50PIRWH | PIR | 50 W | 4000 K | 4000 lm | 80 lm/W |
| FLD50WH | Standard | 50 W | 4000 K | 4000 lm | 80 lm/W |

| PACKAGING | |
|------------------------------|------------|
| Packaging Type | Colour Box |
| Individual unit gross weight | 671 g |
| Pallet Layer Qty | 100 |
| Pallet Layers | 4 |
| Pallet Qty | 400 |
| MOM / OPQ | 1 / 10 |

