



## Cassi


Cassi circular black IP54 bulkhead opal diffuser 14W LED 4000K

### DESCRIPTION

Cassi circular compact bulkhead range offers a practical solution for areas requiring a small bulkhead design ideal for utility areas for wall or ceiling mounted available in two sizes to suit different output requirements

### FEATURES

- Stainless Steel captive fixing screws
- Polycarbonate diffuser
- 20mm cable entry on back of fitting
- Push fit terminal block



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.5 kg
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	ABS
Construction Materials Line 2	PC	Dimensions - Height	230 mm
Dimensions - Width	230 mm	Dimensions - Depth	51 mm

### PRODUCT INFORMATION

Wattage Combined	14W	CCT Combined	4000K
Luminaire Lumens Combined	1570 lm	lm/W Combined	112 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP54	IK Rating	IK08





IP54



IK08

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KCAS14BKFL	Standard	14 W	4000 K	1570 lm	112 lm/W
KCAS14BKLV	Standard	14 W	4000 K	1440 lm	103 lm/W
KCAS14WHFL	Standard	14 W	4000 K	1570 lm	112 lm/W
KCAS14WHLV	Standard	14 W	4000 K	1440 lm	103 lm/W
KCAS8BKFL	Standard	8 W	4000 K	900 lm	112 lm/W
KCAS8WHFL	Standard	8 W	4000 K	905 lm	113 lm/W

## PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	508 g
Pallet Layer Qty	140
Pallet Layers	3
Pallet Qty	420
MOM / OPQ	1 / 20

