



## Colour Temperature Selectable 13W LED Commercial Downlight


Commercial downlight white 200mm diameter 13W LED CCT selectable

### DESCRIPTION

This range is ideal for many applications, with high lumen efficiency for enhanced energy saving and colour temperature selection allowing the desired lighting effect to be chosen on installation.

### FEATURES

- Tough Polypropylene construction
- Colour temperature selectable - options of 3000K/4000K/6000K
- Lumen efficacy of up to 113 lm/W
- Integral terminal connections E- & E+ allow luminaire to be used in 3 hour emergency mode when used with Eterna battery packs
- 165mm hole cut out size



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.26 kg
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polypropylene
Construction Materials Line 2	Polycarbonate	Dimensions - Height	200 mm
Dimensions - Width	200 mm	Dimensions - Depth	95 mm

### PRODUCT INFORMATION

Wattage Combined	13W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	1470 - 1490 lm	lm/W Combined	113 - 115 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		





IP20



Colour Temp.  
Selectable

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KCOMCS13	Standard	13 W	3000 K	1470 lm	113 lm/W
			4000 K	1480 lm	114 lm/W
			6000 K	1490 lm	115 lm/W
KCOMCS18	Standard	18 W	3000 K	2020 lm	112 lm/W
			4000 K	2240 lm	124 lm/W
			6000 K	2130 lm	118 lm/W
KCOMCS8	Standard	8 W	3000 K	890 lm	111 lm/W
			4000 K	920 lm	115 lm/W
			6000 K	900 lm	112 lm/W

## ACCESSORIES

Product Code	Description	MOM / OPQ
EBPM3	Emergency Battery Pack	1 / 10
SEEBPM3	Self-Test Emergency Battery Pack	1 / 10

## PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	363 g
Pallet Layer Qty	100
Pallet Layers	3
Pallet Qty	300
MOM / OPQ	1 / 20

