



## KEM3BULKLI



Maintained IP65 Emergency bulkhead 4W LED 6400K with ISO 7010 legend set

### DESCRIPTION

Rectangular functional maintained emergency bulkhead, able to be adjusted to non-maintained function. An energy efficient 4W solution offering 270 lumens in mains mode and 130 lumens in emergency mode. ISO7010 legend set provided with an option of signs directive available and a recessed frame to suit multiple applications

### FEATURES

- Polycarbonate construction
- Hinged gear tray & push fit terminals
- 20mm gland entries as standard
- Viewing distance 20m
- Facility for remote switching and non-maintained mode
- 270 lm when connected to mains, 130 lm when connected to battery
- Minimum 3 hour functionality in emergency mode
- ISO 7010 legend set included
- 5 year battery warranty - Replacement battery code: EB17



### GENERAL INFORMATION

<b>Light Source</b>	LED	<b>Colour / Finish</b>	White
<b>Application</b>	Internal/External	<b>Mounting Type</b>	Surface
<b>Product Warranty</b>	5 Years	<b>Battery Warranty</b>	5 Years
<b>Net Weight</b>	0.47 kg		

### TECHNICAL INFORMATION

<b>Nominal Voltage</b>	240 V	<b>Frequency</b>	50-60Hz
<b>Class Protection</b>	2	<b>Operating Temperature (Min)</b>	-20 °C
<b>Operating Temperature (Max)</b>	45 °C	<b>Average Rated Life</b>	40,000 h
<b>Number of switching cycles</b>	15,000	<b>Construction Materials Line 1</b>	Polycarbonate
<b>Dimensions - Height</b>	110 mm	<b>Dimensions - Width</b>	390 mm
<b>Dimensions - Depth</b>	70 mm		

### PRODUCT INFORMATION

<b>Wattage Combined</b>	4.5W	<b>CCT Combined</b>	6400K
<b>Luminaire Lumens Combined</b>	250 lm	<b>lm/W Combined</b>	56 lm/w
<b>Beam Angle</b>	120°	<b>CRI</b>	80
<b>SDCM</b>	<6	<b>Lumen Maintenance</b>	0.9
<b>IP Rating</b>	IP65		





IP65

### PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KEM3BULKLI	Emergency	4.5 W	6400 K	250 lm	56 lm/W

### ACCESSORIES

Product Code	Description	MOM / OPQ
EB17	Li-Ion 3.2V 1500mAh Stick Battery	1 / 100
EB23	Li-Ion 3.2V 1000mAh Stick Battery	1 / 10
BFRAME	Semi-Recessed Emergency Bulkhead Frame	1 / 50

### PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	564 g
Pallet Layer Qty	60
Pallet Layers	5
Pallet Qty	300
MOM / OPQ	1 / 10

