




KEM3LIDL
Recessed non-maintained emergency
downlight 2W LED 160lm with white silver and
black bezel

DESCRIPTION

Highly versatile emergency downlight offering 160lm in emergency mode and includes 3 bezels to suit different ceiling styles. 5 year warranty battery pack and electronic convertor built into one module enables a compact and simple solution for commercial office environments

- FEATURES**
- White, matt silver and black bezels included
 - LiFePO4 Lithium battery technology offering reduced energy consumption, enhanced charging cycle capacity & improved operational life compared to standard NiCad products
 - Optic designed for open area and escape route lighting
 - Built-in battery overcharge protection
 - Integrated green charging indicator LED
 - 160 lm in emergency mode
 - 3 hour non maintained operation
 - Li-Ion 3.2V 1500mAh battery 5 year warranty - Replacement battery code: EB19



GENERAL INFORMATION

| | | | |
|------------------|----------|------------------|----------|
| Light Source | LED | Colour / Finish | White |
| Application | Internal | Mounting Type | Recessed |
| Product Warranty | 5 Years | Battery Warranty | 5 Years |
| Net Weight | 0.2 kg | | |

TECHNICAL INFORMATION

| | | | |
|----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage | 240 V | Frequency | 50Hz |
| Class Protection | 2 | Average Rated Life | 40,000 h |
| Number of switching cycles | 15,000 | Construction Materials Line 1 | Polycarbonate |
| Dimensions - Height | 60 mm | Dimensions - Width | 60 mm |
| Dimensions - Depth | 25 mm | | |

PRODUCT INFORMATION

| | | | |
|---------------------------|--------|------------------------|---------|
| Wattage Combined | 2W | CCT Combined | 6300K |
| Luminaire Lumens Combined | 160 lm | lm/W Combined | 80 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.8 |
| IP Rating | IP20 | Emergency Lumen Output | 165 lm |



PHOTOMETRICS

| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
|--------------|--------------|-------|--------|------------------|---------|
| KEM3LIDL | Emergency | 2 W | 6300 K | 160 lm | 80 lm/W |

ACCESSORIES

| Product Code | Description | MOM / OPQ |
|--------------|-----------------------------------|-----------|
| EB19 | Li-Ion 3.2V 1500mAh Stick Battery | 1 / 100 |

PACKAGING

| | |
|------------------------------|------------|
| Packaging Type | Colour Box |
| Individual unit gross weight | 253 g |
| Pallet Layer Qty | 280 |
| Pallet Layers | 4 |
| Pallet Qty | 1,120 |
| MOM / OPQ | 1 / 40 |

