



## KEM3ML

Maintained IP65 Emergency bulkhead 4W LED 6400K with ISO 7010 legend




## DESCRIPTION

Rectangular functional maintained emergency bulkhead, able to be adjusted to non-maintained function. An energy efficient 4W solution offering 270 lumens in mains mode and 130 lumens in emergency mode. ISO7010 legend set provided with an option of signs directive available and a recessed frame to suit multiple applications

## **FEATURES**

- · Polycarbonate construction
- · 20mm gland entries as standard
- · Minimum 3 hour functionality in emergency mode
- · Facility for remote switching and non-maintained mode
- 270 lm when connected to mains, 130 lm when connected to battery
- Ni-Cd 3.6V 800mAh battery 1 year warranty Replacement battery code: EB21
- ISO 7010 legend set included
- · Viewing distance: 20m





GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Net Weight	0.6 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	110 mm	Dimensions - Width	355 mm
Dimensions - Depth	70 mm		

PRODUCT INFORMATION			
Wattage Combined	4W	CCT Combined	6400K
Luminaire Lumens Combined	270 lm	lm/W Combined	68 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.9
IP Rating	IP65	Emergency Lumen Output	270 lm











PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
КЕМ3ML	Emergency	4 W	6400 K	270 lm	68 lm/W

P65

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB17	Li-Ion 3.2V 1500mAh Stick Battery	1 / 100
EB21	Ni-Cd 3.6V 800mAh Battery	1 / 100
BFRAME	Semi-Recessed Emergency Bulkhead Frame	1/50

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	586 g	
Pallet Layer Qty	60	
Pallet Layers	5	
Pallet Qty	300	
MOM / OPQ	1 / 10	







