



## Compact Emergency LED Exitbox

Maintained or non-maintained Exit box 4W LED 6000K with ISO 7010 up legend



### DESCRIPTION

Low energy compact alternative to standard emergency exit signs, robust steel construction with traditional battery test button for easy access, suitable to be adjusted for non-maintained operation to suit a number of commercial and industrial applications

### FEATURES

- Steel construction
- Push fit terminals
- 3 hour maintained mode as standard which can also be configured for non maintained operation. Facility for remote switching
- Li-Ion 3.2V 1500mAh battery 5 year warranty - Replacement battery code: EB17
- Full range of interchangeable polycarbonate ISO 7010 legends available, comes complete with up arrow legend
- Diffuser on base for illumination of exit path
- Viewing distance: 29m
- LED charge light and battery test button

### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.75 kg		

### TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Construction Materials Line 1	Polycarbonate	Dimensions - Height	180 mm
Dimensions - Width	300 mm	Dimensions - Depth	40 mm
IP Rating	IP20		

### PRODUCT INFORMATION

Wattage Combined	4W	CCT Combined	6200K
Luminaires Lumens Combined	70 lm	lm/W Combined	18 lm/w
Beam Angle	120°	Emergency Lumen Output	85 lm
Dimmable	Not Dimmable		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KEXIT3MLI	Emergency	4 W	6200 K	70 lm	18 lm/W

## ACCESSORIES

Product Code	Description	MOM / OPQ
EB17	Li-Ion 3.2V 1500mAh Stick Battery	1 / 100
EB25	Li-Ion 3.2V 1000mAh Stick Battery	1 / 10

## PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	756 g
Pallet Layer Qty	140
Pallet Layers	3
Pallet Qty	420
MOM / OPQ	1 / 20

