



12W Colour Temperature Selectable Recessed LED Flat Downlight

Recessed flat white 175mm commercial downlight 12W CCT selectable

DESCRIPTION

This range is ideal for many applications, with high lumen efficiency for enhanced energy saving and colour temperature selection allowing the desired lighting effect to be chosen on installation

FEATURES

- Colour temperature selectable – options of 3000K, 4000K & 6000K easily set by a dip switch on the back of the fitting
- Flame retardant aluminium housing with polycarbonate diffuser, includes spring clips to fix within the ceiling
- Slim profile design to allow installations with narrow ceiling voids
- Unobtrusive design with neutral white trim
- Multiple LED low power array: even, shadow free diffused light output
- Flicker free operation
- Lumen efficacy of up to 109 lm/w
- 155mm hole cut out size

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.26 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	Polycarbonate	Dimensions - Height	18 mm
Dimensions - Width	175 mm	Dimensions - Depth	175 mm

PRODUCT INFORMATION

Wattage Combined	12W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	1250 - 1250 lm	lm/W Combined	104 - 104 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP44		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KFLATDL12	Standard,175mm	12 W	3000 K	1250 lm	104 lm/W
			4000 K	1300 lm	108 lm/W
			6000 K	1250 lm	104 lm/W
KFLATDL18	Standard,240mm	18 W	3000 K	1900 lm	106 lm/W
			4000 K	1970 lm	109 lm/W
			6000 K	1900 lm	106 lm/W
KFLATDL24	Standard,300mm	24 W	3000 K	2500 lm	104 lm/W
			4000 K	2530 lm	105 lm/W
			6000 K	2520 lm	105 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	309 g
Pallet Layer Qty	240
Pallet Layers	3
Pallet Qty	720
MOM / OPQ	1 / 30

