



30W IP65 Floodlight


30W black IP65 Floodlight LED 2800lm 4000K

DESCRIPTION

30W IP65 Floodlight

FEATURES

- Aluminium body with tempered glass diffuser
- Pre-wired with 22cm 3 core flex
- Quick fix bracket



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.39 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Aluminium
Construction Materials Line 2	Glass	Dimensions - Height	139 mm
Dimensions - Width	158 mm	Dimensions - Depth	21 mm

PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	4000K
Luminaire Lumens Combined	2800 lm	lm/W Combined	93 lm/w
Beam Angle	110°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP65		





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KFLD10	Standard	10 W	4000 K	900 lm	90 lm/W
KFLD20	Standard	20 W	4000 K	1800 lm	90 lm/W
KFLD30	Standard	30 W	4000 K	2800 lm	93 lm/W
KFLD50	Standard	50 W	4000 K	4500 lm	90 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
KFLDPIR	PIR Attachment for KFLD	1 / 100

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	428 g
Pallet Layer Qty	180
Pallet Layers	7
Pallet Qty	1,260
MOM / OPQ	1 / 30

