
Spec Sheet KFLDPIR





PIR Attachment for KFLD

PIR Attachment for KFLD

DESCRIPTION

PIR Attachment for KFLD

FEATURES

- Vertically and horizontally adjustable PIR
- Time on adjustment: 10 sec ± 3 sec – 7 min ± 2 min
- Lux level adjustments: 5 Lux ~ 2000 Lux
- 120° detection angle
- 10 metre detection range

GENERAL INFORMATION			
Colour / Finish	Black	**Application**	External
Mounting Type	Surface	**Product Warranty**	5 Years
Net Weight	0.05 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	76 mm	**Dimensions - Width**	64 mm
Dimensions - Depth	48 mm	**IP Rating**	IP65

PRODUCT INFORMATION	
Wattage Combined	50W

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	59 g
Pallet Layer Qty	900
Pallet Layers	4
Pallet Qty	3,600
MOM / OPQ	1 / 100

5 Year Warranty

IP65