

2FT IP65 Nano Utility Batten



2ft 15W 1800lm 4000K IP65 Nano Utility Fitting

DESCRIPTION

Slim profile batten available in 600mm, 1200mm and 1800mm, offering even light distribution, single end cable entry through an IP gland with push fit terminals for easy installation supplied with ceiling wall clips

FEATURES

- Tough Polycarbonate Construction
- Push fit terminal connections for quick installation
- Cable gland included
- 2 brackets included for wall and ceiling fixing



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.2 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	38 mm	Dimensions - Width	48 mm
Dimensions - Depth	600 mm	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	15W	CCT Combined	4000K
Luminaire Lumens Combined	1835 lm	lm/W Combined	122 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS





Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,000
Chromaticity coordinates x	0.382	Chromaticity coordinates y	0.376
Stroboscopic effect metric (SVM)	0	Flicker Metric (pst)	0.5
R9 colour rendering index	17	Survival factor @6000hrs	0.9
Spectrum report available	Yes	Displacement Factor	0.94
CCTI/WATTI: Rated Peak Intensity	442 cd		





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KNANOIP2FT	2ft	15 W	4000 K	1835 lm	122 lm/W
KNANOIP4FT	4ft	22 W	4000 K	2550 lm	116 lm/W
KNANOIP5FT	5ft	25 W	4000 K	3070 lm	123 lm/W

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	247 g
Pallet Layer Qty	120
Pallet Layers	4
Pallet Qty	480
MOM / OPQ	1 / 20

