Spec Sheet KNANOIP4FT

eterna.

5 Year Warranty

IP65



4FT IP65 Nano Utility Batten


4ft 20W 2550lm 4000K IP65 Nano Utility Fitting


DESCRIPTION

Slim profile batten available in 600mm, 1200mm and 1800mm, offering even light distribution, single end cable entry through an IP gland with push fit terminals for easy installation supplied with ceiling wall clips

FEATURES

- Tough Polycarbonate Construction
- Push fit terminal connections for quick installation
- Cable gland included
- 2 brackets included for wall and ceiling fixing





GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal/External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.3 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50-60Hz
Class Protection	2	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	50,000 h
Number of switching cycles	25,000	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	38 mm	**Dimensions - Width**	48 mm
Dimensions - Depth	1200 mm	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	22W	**CCT Combined**	4000K
Luminaire Lumens Combined	2550 lm	**lm/W Combined**	116 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

CE

UKCA

Member of theLIA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet KNANOIP4FT

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	4,000
Chromaticity coordinates x	0.385	**Chromaticity coordinates y**	0.382
Stroboscopic effect metric (SVM)	0.0	**Flicker Metric (pst)**	0.5
R9 colour rendering index	8.0	**Survival factor @6000hrs**	0.9
Claim LED Replace Fluorescent	FALSE	**Spectrum report available**	Yes
Displacement Factor	0.91	**CCT1/WATT1: Rated Peak Intensity**	734 cd

5 Year Warranty

IP65

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
KNANOIP2FT	2ft	15 W	4000 K	1835 lm	122 lm/W
KNANOIP4FT	4ft	22 W	4000 K	2550 lm	116 lm/W
KNANOIP5FT	5ft	25 W	4000 K	3070 lm	123 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	355 g
Pallet Layer Qty	60
Pallet Layers	4
Pallet Qty	240
MOM / OPQ	1 / 20

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D