

4FT IP65 Nano Utility Batten



4ft 20W 2550lm 4000K IP65 Nano Utility Fitting

DESCRIPTION

Slim profile batten available in 600mm, 1200mm and 1800mm, offering even light distribution, single end cable entry through an IP gland with push fit terminals for easy installation supplied with ceiling wall clips

FEATURES

- Tough Polycarbonate Construction
- Push fit terminal connections for quick installation
- Cable gland included
- 2 brackets included for wall and ceiling fixing



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.3 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	38 mm	Dimensions - Width	48 mm
Dimensions - Depth	1200 mm		

PRODUCT INFORMATION

Wattage Combined	22W	CCT Combined	4000K
Luminaire Lumens Combined	2550 lm	lm/W Combined	116 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP65		





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KNANOIP2FT	Standard	15 W	4000 K	1835 lm	122 lm/W
KNANOIP4FT	Standard	22 W	4000 K	2550 lm	116 lm/W
KNANOIP5FT	Standard	25 W	4000 K	3070 lm	123 lm/W

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	355 g
Pallet Layer Qty	60
Pallet Layers	4
Pallet Qty	240
MOM / OPQ	1 / 20

