



Li-Ion LED Emergency Twinspot

Compact internal white emergency twinspot
2 x 2W LED 6300K

DESCRIPTION

Reduced battery capacity requirement allows a more compact design reducing the weight dramatically compared to traditional products facilitating easier installation, an ideal choice for internal applications requiring practical emergency lighting

FEATURES

- Polycarbonate construction
- Individual indicator to show 'Lamps Healthy' and 'Charge'
- Horizontally and vertically adjustable heads, 180° rotation across the horizontal plane
- 3 hour duration in emergency mode
- Li-Ion 3.2V 4500mAh battery 5 year warranty - Replacement battery code: EB18
- Push fit terminals

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.52 kg		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50–60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	20,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	285 mm	Dimensions - Width	250 mm
Dimensions - Depth	50 mm	IK Rating	IK08
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	4W	CCT Combined	6400K
Luminaire Lumens Combined	450 lm	lm/W Combined	113 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7



Emergency Lumen Output	450 lm	Dimmable	Not Dimmable
CCT1/WATT1: Rated Peak Intensity	160 cd		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
KTWINSPLI	Emergency	4 W	6400 K	450 lm	113 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EBI8	Li-Ion 3.2V 4500mAh Side-by-Side Battery	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	763 g
Pallet Layer Qty	120
Pallet Layers	2
Pallet Qty	240
MOM / OPQ	1 / 20

