Spec Sheet LBAT4FTEM3

5 Year Warranty

IP20



LED Batten

4ft 23W 4200K LED Batten with Emergency


DESCRIPTION

4ft LED highly efficient traditional style batten fixture, slim profile design with even light distribution, front diffuser and end caps removable to allow for easy wiring at either end of the batten or Besa mounting from the rear of the fitting, comes complete with bolt on Emergency downlight attached at the end of the fitting

FEATURES

- Full photometric data available to enable lighting designs. Light output is equivalent or superior to traditional fluorescent battens.
- Pressed steel body and polycarbonate diffuser
- LED tray can be removed from the housing for easy installation
- 20mm knockout glands at each end for through wiring options
- BESA box mounting
- Gear tray retaining straps
- Push terminal connections
- 3 hour duration in emergency mode

Li-Ion Emergency Box



GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal	**Mounting Type**	Surface
Product Warranty	5 Years	**Battery Warranty**	1 Year
Net Weight	1.67 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	35,000 h
Number of switching cycles	15,000	**Construction Materials Line 1**	Steel
Construction Materials Line 2	Polycarbonate	**Dimensions - Height**	73 mm
Dimensions - Width	60 mm	**Dimensions - Depth**	1170 mm
IP Rating	IP20		

PRODUCT INFORMATION			
Wattage Combined	23W	**CCT Combined**	4200K
Luminaire Lumens Combined	2930 lm	**lm/W Combined**	127 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet LBAT4FTEM3

5 Year Warranty

IP20

Emergency Lumen Output	118 lm	**Lighting Technology used**	LED
Non-Directional or Directional	NDLS	**Mains or non-mains**	MLS
Connected light source (CLS)	FALSE	**Colour tuneable light source**	FALSE
High Luminance light source	FALSE	**Anti Glare shield**	FALSE
Dimmable	Not Dimmable	**CCT1/WATT1: Rated Peak Intensity**	810 cd

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
LBAT4FTEM3	Emergency	23 W	4200 K	2930 lm	127 lm/W
LBAT6FTEM3	Emergency	48 W	4200 K	6000 lm	125 lm/W

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
EB2	Ni-Cd 3.6V 2000mAh Stick Battery	1 / 1

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	1,960 g
Pallet Layer Qty	24
Pallet Layers	7
Pallet Qty	168
MOM / OPQ	1 / 1