



Lithium Ion Emergency LED Downlight


Recessed non-maintained emergency 2W LED 160lm with white, matt silver, black bezel

DESCRIPTION

Highly versatile emergency downlight offering 160lm in emergency mode and includes 3 bezels to suit different ceiling styles. 5 year warranty battery pack and electronic convertor built into one module enables a compact and simple solution for commercial office environments

FEATURES

- White, matt silver and black bezels included
- LiFePO4 Lithium battery technology offering reduced energy consumption, enhanced charging cycle capacity & improved operational life compared to standard NiCad products
- Optic designed for open area and escape route lighting
- Built-in battery overcharge protection
- Integrated green charging indicator LED
- 160 lm in emergency mode
- Li-Ion 3.2V 1500mAh battery 5 year warranty - Replacement battery code: EB19



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.2 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Average Rated Life	40,000 h
Construction Materials Line 1	Polycarbonate	Dimensions - Height	210 mm
Dimensions - Width	60 mm	Dimensions - Depth	60 mm
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	2W	Luminaire Lumens Combined	160 lm
lm/W Combined	80 lm/w	Beam Angle	120°
Emergency Lumen Output	160 lm		





IP20

PHOTOMETRICS

Product Code	Product Type	Watts	Luminaire lumens	Lm/W
LDLEM3LI	Emergency	2	160 lm	80 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	251 g
Pallet Layer Qty	280
Pallet Layers	4
Pallet Qty	1,120
MOM / OPQ	1 / 40

